Welcome to our interactive version of Nitrogen+Syngas Issue 350

Please use either the buttons on the left or top right of the page to navigate your way around this interactive PDF

IMPORTANT INFORMATION:

5

10

11

12

13

14

15

16 17

18

19

20 21

22 23 24

25 26

27 28 29

30 31 Copyright – Issued six times per year, or bi-monthly. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, mechanical, photocopying, recording or otherwise – without the prior written permission of the Copyright owner.

November | December 201

Number 350

www.nitrogenandsyngas.com

Power to ammonia

Prospects for Indian urea

Fertilizers from gasification

Nitrate plant debottlenecking

CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

NITROGEN+SYNGAS ISSUE 350 NOVEMBER-DECEMBER 2017

BCInsight

Southbank House, Black Prince Road London SE1 75J, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com



Making a difference to the world around us

25

26

27

28

29

30

31

With years of operating experience and expertise across the syngas, petrochemical, oil and gas markets, Johnson Matthey continues to invest in technologies that improve processes whilst looking after the environment.

Our gas heated reforming technology is a proven energy efficient solution for syngas generation across and raw water consumption, whilst maximising

Contact us to find out how our technology can benefit your business.

Cover: Offshore wind farm. Eugene Suslo/Shutterstock.com



Expansion in Russia A new ammonium nitrate plant for SDS-Azot



Ammonia synthesis in China The country's largest inert-free ammonia synthesis loop.







CONTENTS

10 Power to ammonia

> Making ammonia from hydrogen generated by electrolysis of water has a long history, and today, coupled with renewable electricity, offers the prospect of a carbon neutral source of ammonia. But can the economics possibly stack up?

- 14 The prospects for Indian urea India has unveiled plans to end urea imports by 2022. However, many such pronouncements have come and gone over the years - is this one any more likely to come to fruition?
- 18 Major investments in Russia's nitrogen production Eugene Gerden reports on the continuing growth in Russian nitrogen fertilizer production, as SDS-Azot begins work on a new line for production of ammonium nitrate at Kemerovo.
- **19** Ammonia market developments A look at some of the factors shaping merchant ammonia supply, demand and patterns of trade worldwide.
- 20 Safety in ammonia plants A report on papers presented at the 62nd Safety In Ammonia Plants and Related Facilities Symposium, held in September in New York.
- 21 Fertilizer production via the gasification route N. Mangukia of Linde Engineering India discusses the benefits of large scale ammonia/urea plants based on the gasification of coal or petcoke for countries like India.
- 22 A China first at Henan Jinkai ammonia plant M. Rizzi of Casale and Xu Junhong of Henan Jinkai Group report on the design behind the largest single-train inert-free ammonia synthesis loop built and operating to date: the 2,000 t/d Henan Jinkai ammonia plant in Kaifeng, China.
- 24 Driving methanol plant efficiency M. Janardhanan of Johnson Matthey outlines where gas heated reformer technology has come from and where it is heading to, highlighting the benefits of its use in different applications, particularly in Iran where water consumption is very important.
- 26 Nitrate plant debottlenecking and modernisation Casale has wide experience of many different types of plants thanks to its revamping activities. J. F. Granger of Casale discusses the latest trends for the modernisation of nitrate plants.
- 28 From low cost by-product to premium AS granules thyssenkrupp Industrial Solutions (tkIS) has developed a new fluidised bed granulation process to convert low cost by-product ammonium sulphate solutions into premium grade granules. J. Mathiak of tkIS, describes the process and reports on the current status of the technology.

7

8

Syngas News

People/Calendar

Plant Manager+

Problem No. 45: Effect on reactor

liner in case of reactor hold up

REGULARS

- 3 Editorial Nitrogen fixing gathers pace 4
 - Price Trends 9 Market Outlook
- 5 6 Nitrogen Industry News



CONTENTS What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking



BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com



www.jmprotech.com

Nitrogen fixing gathers pace

We've reported before on attempts to spread the nitrogen fixing ability of plants like legumes to staple food crops like cereals. Allowing such nitrogen-hungry plants to absorb that nitrogen directly from the air around them in the same way that they do carbon dioxide is something of a holy grail for bioscience companies, and could have the potential to radically reshape the artificial nitrogen fertilizer industry – currently the market for 75% of the 180 million tonnes of ammonia consumed every year.

[This] could have the potential to radically reshape the artificial nitrogen fertilizer industry.

12

13

14

18

21

22

23

24

25

26

27

28

29

30

projects to try and see if cereal crops can be persuaded somehow to mimic legumes' ability to 'fix' atmospheric nitrogen, many involving inoculating plant roots with the same nitrogen-fixing bacteria that legumes use. Inoculation is already used in legumes to boost their own nitrogen-fixing ability. However, the major development in the field which happened last month was that German chemical giant Bayer announced that its LifeSciences division would be partnering with American biotechnology company Gingko Bioworks to launch a new \$100 million - so far unnamed - agricultural technology start-up company, bringing the knowledge resources and corporate financial muscle of Bayer to bear on the problem. Bayer says that the new company "will focus on transformational beneficial microbes for plants to provide growers with next generation solutions to their biggest challenges. Initial activities will focus on nitrogen fixation, minimising agriculture's environmental impact. The work combines the synthetic biology leadership of Ginkgo Bioworks with Bayer's deep knowledge and experience in agriculture and microbial products."

The key to legumes' remarkable ability to fix atmospheric nitrogen comes from a symbiotic relationship with a class of bacteria call rhizobia which congregate in the plants' root nodules. The bacteria lie dormant in the soil, but in the presence of the right kind of plants infect the roots and absorb organic acids from the plant as their food and energy source, in return converting nitrogen into ammonium ions, which the plants can process into amino acids and other useful molecules. What the Bayer-Gingko team will be trying to determine is what makes legume roots attractive to the bacteria, and whether this property can be duplicated in



other plants, perhaps by genetic engineering. Bayer says that it already has an extensive collection of microbes which it knows work well with particular crops, and Gingko will be helping to modify these to see if they can duplicate the nitrogen fixing properties of rhizobia.

The advantage for famers in places like Africa, where fertilizer can be scarce and expensive, is pretty clear. But at the moment there are still questions about nitrogen leaching. This is, apparently, not just a bane of fertilizer nitrogen over-application. Most nitrogen-fixing crops also produce excess nitrogen which can leach into the environment in a similar way.

But Bayer and Gingko are not the only companies working on this problem. A different approach is being investigated by Plant Genetic Engineering Inc. associated with Stony Brook University. New York. Here the aim is to engineer plants' own cells with the genes that encode the enzymes needed for nitrogen fixation and nitrification. This is already done by cyanobacteria, and Plant Genetic Engineering hope to be able to introduce cyanobacteria into plants in the same way that chloroplasts - the parts of plant cells which conduct photosynthesis - were originally incorporated by plants. Chloroplasts are descended from bacteria that once lived independently of plant cells. At the moment the focus is not on cereal crops but tobacco, mainly because the tobacco plant genome is already well characterised and understood.

The promise of nitrogen-fixing cereal crops is clearly understandable. However, the technical challenges are also clearly equally formidable. Nevertheless, the news that Bayer is willing to commit significant resources to its development is an indication that this is an area to watch

Richard Hands, Editor



Melamine

WE ARE

MELAMINE

TECHNOLOGY

is a key presence in our lives.

Euromel® melamine is extensively used in the Chinese bullet trains for its superior performance.

Driver's cab, switch cabinets, engine rooms, doors and sidewalls rely on melamine to feature insulation and fire resistant characteristics.

Euromel® is the trademark for melamine produced at plants licensed, engineered and implemented by ET Eurotecnica Group, the leading melamine technology provider since 1978.

Euromel® is sign of top melamine quality, as licensees the likes of QAFCO, MHTL, Grupa Azoty ZAP, KHPC, XLX Fertilizers, Hubei Yihua Chemical, Zhong Yuan Dahua can confirm.

Across the years ET Eurotecnica Group has been committed to developing the melamine industry from one playing a marginal role to a global business worth 2 billion USD.

Ask for more information. Visit us on www.igoforEUROMEL.com



CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian <u>urea</u>

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

NITROGEN+SYNGAS ISSUE 350 NOVEMBER-DECEMBER 2017

BCInsight

Southbank House, Black Prince Road London SE1 75J, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com



Price trends



13

18

23

25

27

28

MARKET INSIGHT

Laura Cross, Senior Analyst, Integer Research, assesses price trends and the market outlook for nitrogen.

NITROGEN

A steady string of Indian urea import tenders have provided important price markers for the industry in recent months, in the face of temporarily reduced supply from some key exporters. A purchase tender was announced on 1 September by Indian Potash Limited (IPL), under which it received 325,000 tonnes of its desired 500,000 tonnes. The tender closed on 8 September for shipment by 23 October. The lowest offer was from Comzest at \$241.22/tonne c.fr for west coast India and \$251/tonne c.fr for east coast India from Amber. IPL made a counter offer of \$246.91/tonne c.fr for east coast India and matched Comzest's offer of \$241.22/t c.fr for west coast. The final price was settled at \$245.50/tonne c.fr. Only 11 offers were made, totalling 729,000 tonnes, because of lack of availability out of Arab Gulf countries including Iran and Saudi Arabia, and higher margin sales into other markets such as Turkey.

In mid-September, the urea price soared by another \$20-30/t in the space of a week when IPL announced another import tender on 16 September, for shipment by 8 November. This unexpectedly early tender prompted prices ideas from the Arab Gulf of around \$270/t f.o.b., followed by Egyptian sales to the Americas

Cash equivalent	mid-Sept	mid-July	mid-May	mid-Ma
Ammonia (\$/t)				
f.o.b. Caribbean	200	205	285	295
f.o.b. Arab Gulf	230-260	180-190	295	350
c.fr N.W. Europe	240-260	230-250	325	365
c.fr India	240-270	209-240	340	360
Urea (\$/t)				
f.o.b. bulk Black Sea	224-234	181-190	175	237
f.o.b. bulk Arab Gulf*	227-232	153-187	176	211
f.o.b. bulk Caribbean (granular)	190-198	160-183	210	218
f.o.b. bagged China	248-255	207-212	210	231
DAP (\$/t)				
f.o.b. bulk US Gulf	333-337	344	355	375
UAN (€/t)				
f.o.t. ex-tank Rouen, 30%N	141-143	133-137	157	169

purchase by IPL.

at around \$300/t f.o.b. IPL received 16 offers for a total of 1.1 million tonnes of urea under the mid-September tender. The lowest offers received were from Aries at \$284.66/t c.fr for east coast India, and from Transagri at \$285/t c.fr for west coast. These prices were almost \$40/t higher than the previous tender, continuing the price momentum and tight seasonal supply caused by maintenance turnarounds and contract commitments from

the usual sellers to India The Indian government amended its urea import policy conditions in late-September in order to ensure domestic requirements. On 26 September 2017, the government extended import licenses to two urea producers - Rashtriya Chemicals & Fertilizers (RCF) and National Fertilizer Limited (NFL). Previously, only STC, MMTC and IPL were permitted to issue import tenders. RCF issued its first import tender on 14 October, receiving 17 offers totalling 1.4 million tonnes. The lowest offers received were from Aries at \$290.66/t c.fr for east coast delivery, and from Fertrade at \$291.72/t c.fr for west coast. RCF ultimately sourced 426,000 tonnes of urea under the tender from a combination of Middle East, Chinese and Baltic sellers, at prices around \$5/tonne than the previous

The global nitrogen market remains in a state of oversupply, although prices looked firmer in Q3 2017 as the market entered a period of seasonal demand and China remained largely out of the export market. Despite the short-term improved price sentiment, the market still remains in a fundamentally weak state with new capacity additions in the rest of 2017 forecast to keep the market in oversupply. Urea prices were more stable in Q2 and Q3 2017 than at the start of the year, driven primarily by the noteworthy reduction in Chinese export volume which kept price ideas to seasonal a buyers firmer than they would have been

otherwise

Typical urea ex-works costs per tonne increased or remained flat in all regions in our sample except Ukraine, where the region continued to benefit from gas diversification and depreciation of the hryvnia. Typical urea producer unit margins grew by an average of 27% between May and August 2017.

Through the early part of 2017, the Chinese government eased production restrictions on coal, leading to price decreases, but more recently, restrictions have come back into play, causing anthracite and thermal prices peaking at their highest levels of 2017. There are suggestions that the Chinese government may reduce operating rates of industrial enterprises (including urea plants) in Northeast China by up to 50% ea during the winter heating season to alleviate further upward pressure on coal prices.

In contrast, the ammonia price decreased steadily throughout Q2 2017 and into Q3 following a tighter Q1 2017 as a result of temporary supply outages. The Tampa ammonia price was settled at a \$25/tonne increase in September and other benchmarks followed suit in prepartion for refill application buying.

September marked a turning point in ammonia price sentiment, as price ideas began to improve due to stronger demand in the face of several supply interruptions to key ammonia exporters.

Following a three-month period of consecutive price decreases that began in May, the Yuzhny Black Sea ammonia price broke the \$200/t f.o.b. boundary in mid-September, before swiftly moving towards \$220/t by the end of the month. The Tampa contract price increased by \$30/t between September and October, increasing to \$245/t c.fr. Although this price increase was larger than expected, the ammonia price remains drastically below other nitrogen products on a nutrient value basis.



XINJIANG XLX GO FOR A TWIN!

Just a few months after the successful commissioning of a new melamine plant based on Eurotecnica's newest 4th generation Euromel® Melamine Process, Xinjiang Xinlianxin Energy Chemical Co.Ltd. has once again selected the most reliable, efficient and friendly-to-environment melamine technology in the world.

Same as for the first plant, this second one shall have a nameplate capacity of 60,000 MTPY featuring the world's largest single high-pressure reactor.

Combined with the lowest energy consumption, reduced investment and the traditional total zero pollution, this new project is the evidence of how advanced the ultimate achievements of G4 Euromel® Melamine Process are. The number of licensed Euromel® Melamine plants goes up to 21 units. The list of licensees includes companies the likes of Qatar Qafco, Methanol Holding Trinidad, Hubei Yihua, Zhong Yuan Dahua, Petrochina, Grupa Azoty ZAP, KHPC and several other, making of Eurotecnica Group the undisputed technology leader in the melamine industry.

Ask for more information. Visit us on www.igoforEUROMEL.com

EUROMEL[®]

MELAMINE

TECHNOLOGY





CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

NITROGEN+SYNGAS ISSUE 350 NOVEMBER-DECEMBER 2017

BCInsight

Southbank House, Black Prince Road London SE1 75J, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

www.nitrogenandsyngas.com





18

23

24

25

28

29

30









MARKET INSIGHT Mike Nash, Global Business Director, IHS Chemical, assesses the market for methanol.

METHANOL

tion rates improved and logistics issues Methanol prices increased further in Sepwere resolved. We will likely see a late tember. Asian prices traded \$40 higher, year bump in demand from reconstrucin range of \$315-355/t. c.fr: China avertion efforts in Texas and Florida related to age prices were up \$42 at \$312.5-355/t, wood products as well as derivatives used c.fr. Methanex's posted APCP for October in home appliance manufacturing and coatis \$400/t, an increase of \$50/t over its ings demand via MMA. Additionally, as up posted price for September. European spot to one million vehicles are estimated to prices (T2 f.o.b. Rotterdam) for September have been destroyed in Houston alone, were €9 higher than up their August level at this will lead to high new car sales in Sep-€267/t over the month. Methanex posted tember and 40 2017. its 4Q 2017 West European Contract Price In India, port prices started the month at €330/t. f.o.b. Rotterdam T2. an increase at an average of \$292.5/t c.fr T1 and finof €10 on the previous guarter. The 40 ished the month \$42.5 higher at \$335/t: 2017 West European Contract Price was domestic prices increased from 25 Rs/kg to settled at €318/t, f.o.b. Rotterdam T2, up 26.5 Rs/kg during the month. The increase was due to operational issues in the Mid-€3/t from 3Q 2017. The ongoing suspension of duty on methanol arriving into the dle East, higher prices in China and rising EU implemented by the European Commisdomestic demand. European demand was stable in August. Demand into formaldehyde

the second half of September, as produc-

majeure at a facility in Germany. Biodiesel

In China, methanol consumption in the

sion is likely to remain for the foreseeable future. The official, posted reference prices saw a seasonal decline and an ongoing force from the two main US producers for October were \$1.19/gal for Methanex (up 3 demand was stable at low levels, due to cents from September) and \$1.14/gal for pressure from low crude oil prices, which Southern Chemical Co. (a rollover), equivamake it less competitive against traditional lent to \$396/t and \$379/t respectively. diesel. Acetic acid demand was steady at In operations, global utilisation rates good levels, with all major regional producin September were around 2% lower than ers running. Rhine water levels started and August 2017, at around 67% of nameplate ended the month at a relatively low level capacity or 80% of effective capacity, with of 142 cm, despite rising to 248 cm on 4 unexpected outages in the Middle East and September and 223 cm on 15 September. US production units impacted by Hurricane Below a level of around 160 cm, barges have Harvey. In Iran, natural gas restrictions conto be short-loaded, increasing unit logistics tinued to constrain operating rates in early costs and tightening barge availability. September. In Saudi Arabia, Ar Razi II, III and IV were offline for most of September due to MTO sector increased during, averaging a a combination of temporary gas shortages high level of around 91%. The MTO section and unexpected operating issues. Trini-

of Fund Energy Changzhou has been offline dad's operating rate in September remained since the end of March, with no re-start around 89%, while Methanex's Chilean unit date announced. Formaldehvde prices continued to be impacted by seasonal gas rose with recovering demand and higher allocations. In China, overall capacity utilisafeedstock prices. DME operating rates tion was very similar to August, at around remained very low. 57% of nameplate capacity or around 74% In Southeast Asia, demand into acetic of effective capacity. A new methanol unit, acid improved in the second half of the Hualu Hengsheng (1.0 million t/a, coal-

month with the re-start of the two major based) began its production trial at the end regional production units after outages. In of September, with commercial production Korea, supply was tight and demand into traditional end-uses was satisfied via term In the Americas, methanol demand into contracts. In Taiwan, supply was tight and methanol demand increased in late September after one of the major domestic

all derivatives, especially acetic acid, was impacted by Hurricane Harvey in the first half of the month: the situation eased in acetic acid units resumed production.

expected in October



Source: BCInsight

AMMONIA

Market outlook

- Seasonal refill demand for ammonia in the US is forecast to keep prices firm until December 2017. Similarly, the recent spate ammonia supply outages looks likely to continue in the shortterm, tightening the supply-demand balance in Q4.
- In Saudi Arabia, the SAFCO IV ammonia and urea plant went offline on 23 September for a scheduled 84-day turnaround which will remove more than 100,000 tonnes of merchant ammonia from the traded market.
- There has been some price firming in 30 2017 due to plant outages, but in 01 2018 ammonia prices are forecast to soften again as planned turnarounds come to an end and seasonal fertilizer demand slows. Prices are expected to remain above \$200/tonne f.o.b., however, as high-cost exporters move away from ammonia towards better-margin products and in doing so, reduce some of the oversupply burden.
- Following the sharp price increases in September and October, the outlook for the remainder of 2017 is uncertain, although prices are expected to reduce from their current levels once Indian buying comes to a close. Lower exports from China have helped keep prices firmer than they might otherwise have been.

UREA

Spring pre-buying in Q1 2018 is expected to stimulate prices somewhat. although developments in regional price benchmarks will be driven by the timing of new project commissioning, such as in the US.

 In Bolivia, the Bulo Bulo granular urea plant moved closer to full completion in October, and government officials from the country's agricultural regulatory agency have carried out final storage facility inspections. Once approval is given, YPFB plans to export around 80% of the urea produced at the 2,100 t/d plant to Brazil, Argentina and Paraguay.

Methanol prices have been rising on a combination of unexpected outages in places such as Saudi Arabia and lack of gas availability in the Middle East. Chile and other regions. Hurricane Harvev also temporarily impacted upon US production.

METHANOL

- · Longer term, the impact of Hurricane Harvey on the Houston area is expected to see a boost to US construction, coatings and new auto buying, which may affect methanol demand into chemical derivatives such as formaldehyde, acetic acid and MMA next year. In the EU, suspension of duty on metha-
- nol imports is set to continue. Chinese MTO production continues to drive merchant demand there, and the knock-on effect of China's dominance in the methanol market is a growing influence on global pricing dynamics, as MTO plants become the global 'buyer of last resort', willing to take methanol at (almost) any price.

www.nitrogenandsyngas.com

CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking



BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

www.nitrogenandsyngas.com

Nitrogen+Syngas 350 | November-December 2017

Nitrogen Industry News

NITROGEN INDUSTRY NEWS

CONTENTS

WE CONVEY QUALITY

High Performance

Bucket Elevators

AUMUND Chain and

Belt Bucket Elevators

and Cement Industry

kind of bulk material

• Efficient transport of any

AUMUND

AUMUND Foerdertechnik GmbH

Saalhoffer Str. 17 • 47495 Rheinberg • Germany

minerals@aumund.de · www.aumund.com

www.nitrogenandsvngas.com

• For the Fertilizer, Minerals

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking



BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

East coast users face gas shortages Australia's east coast gas markets are ing export and/or price controls on LNG facing a shortfall of gas in 2018 of 1.3-2.4 billion cubic metres according to a recent report from the Australian Competi-

tion and Consumer Commission, Although gas is plentiful along Australia's coasts and in some onshore fields, a combination of insufficient east-west pipeline capacity, large new LNG exporters in Queensland and moratoriums on gas exploration and development in states such as Victoria. New South Wales and the Northern Territories mean that there are fears there may not be enough gas for domestic industrial users in future. The government says that it is consider-

UNITED STATES

15

18

22

23

25

28

29

30

31

AUSTRALIA

Stamicarbon acquires 20% stake in Pursell Agri-Tech

Maire Tecnimont says that its Stamicarbon subsidiary has bought a 20% stake in Pursell Agri-Tech, LLC, a US-based start-up company which specialises in developing and marketing polymer-coated, controlledrelease fertilizers. Stamicarbon's investment is put at \$5.5 million. Pursell Agri-Tech, headquartered in Sylacauga, Alabama, has developed a new technology to coat fertilizers at competitive cost levels in order to produce controlled-release fertilizers suitable for efficient fertilization of broad-acre commodity agricultural crops. The technology combines proprietary polymer compositions and a highperformance coating process to deliver a range of controlled-release fertilizers, notably urea, resulting in, the company says, a highly sustainable crop nutrient solution that boosts farmers' yields while also reducing the potential impact on the environment.

Stamicarbon and Pursell have also entered into an industrial cooperation agreement whereby Stamicarbon will be the exclusive global licensing partner, licensing the technology to interested parties outside North America, such as major urea producers, and large fertilizer producers or distributors, while Pursell Agri-Tech will develop with selected dedicated partners the North American market, where Stamicarbon will act as a non-exclusive licensing partner. The parties will also

to resolve the situation if gas exporters and State regulators are not able to work towards reducing the potential shortfall. Among those complaining of the two-tier market, which sees west coast gas prices at around US\$4.90/MMBtu for industrial users, but \$8-13/MMBtu for east coast consumers, are fertilizer producers such as Orica, which operates a 360,000 t/a ammonia plant at Kooragang Island near Newcastle, New South Wales. The company's chief executive Alberto Calderon has called the situation "myopic and unsustainable," and said that his own

work closely together in an open innovation platform on the development of other new businesses and technologies. "This strategic investment opens us a

company was at a "crisis point".

new promising market, such as the coated fertilizers', and represents a new milestone in the Group's strategy of developing innovative technologies adjacent to our core business", commented Pierroberto Folgiero, CEO of Maire Tecnimont Group. Nick Adamchak. Chief Executive Officer of Pursell Agri-Tech said: "Pursell Agri-Tech is delighted to welcome Stamicarbon as a shareholder and to enter into this strategic partnership with them. We're confident it will allow for better fertilizers to become widely available, paving the way for more sustainable climate-smart agriculture worldwide.' Fire at LSB Industries shuts

ammonia plant

LSB Industries was forced to take its Prvor. Oklahoma ammonia plant out of service on September 23rd after a minor fire at the site. The company said that it expected production to resume by the end of October. In the meantime, the unplanned outage will be used to repair damage to electrical controls, wiring and piping. LSB said that no staff were injured, and there was no damage to the reformer or other major equipment items, and no release of ammonia. The company said that it will meet customer commitments for pre-sales of products by either shipping from other facilities or by purchasing them from third parties. As a

result, the ammonia plant downtime will

not result in reductions of urea ammonium nitrate (UAN) or ammonia sales volumes The cost of repairs, together with the cost of buying UAN rather than producing it and the lack of contribution to fixed costs will total around \$1.5-2.0 million in 30 2017 and \$2.5-2.75 million in 40 2017. The company said that it would provide an update on the progress of the repairs and the impacts of the downtime on financial results when the company reported its 30 results in late October.

US nitrogen imports to decrease

Fertecon, part of Informa's Agribusiness Intelligence, says that US imports of nitrogen fertilizer will decrease significantly as 11 million t/a of new domestic nitrogen capacity coming on-line over the next few vears. Between 2015 and 2018, over 11 million t/a of nitrogen fertilizers capacity will enter the US market (3.6 million t/a ammonia. 4.9 million t/a urea and 2.9 million t/a of UAN). This will displace imports from previous key suppliers; ammonia exports from Trinidad to the US have been displaced to markets in Europe. North Africa and even Asia, while Russian exports to the US have dropped sharply.

The coming years are set to see some further seismic shifts in global nitrogen markets as China adjusts to a low growth environment: concerns over pollution of waterways arising from over-application of fertilizer have led the government to target a reduction in growth to 1% per annum to 2020, with 0% as the long-term target. Meanwhile, low energy prices have flattened cost curves, with implications for low and high cost producers alike. In Sub-Saharan Africa, fertilizer demand in has grown at almost 9% per annum on average, and strong growth is forecast to continue, increasing regional fertilizer consumption by over 4 million tonnes over the

coming decade. Alan Pickett, Principal Consultant at Fertecon commented: "With the global fertilizer market experiencing lower prices across the board in the wake of capacity investments made over the last five years. the less efficient producers are being pushed out while others are developing new products to counteract the resulting decline in margins. The restructuring trends are set to continue for the foreseeable future, but the fertilizer industry is cyclical and prices are expected to recover in the years ahead when the impact of recent investments has been absorbed '

INDIA

Start-up for Matix Fertilisers urea plant

Matix Fertilisers & Chemicals says that it has started production at the company's new \$1.1 billion urea plant at Panagarh in West Bengal. The 1.3 million t/a capacity plant, uniquely, uses coalbed methane (CBM) as feedstock. Matix managing director P.R. Dhariwal told local media that the plant is currently operating at 40% capacity, but that it was anticipated that it would ramp up to full capacity by the end of 2017. He added that the plant, located close to the feedstock source as well as the fertilizer consuming region of northeast India, would be key to the fertilizer security of India's north-eastern states. The gas comes from Essar Oil's Raniganj block, with a 30km dedicated pipeline bringing the gas to the ammonia-urea facility. The company has also set up a captive power plant with capacity of 54 MW, which supplies not just the nitrogen complex, but will also be able to supply power to markets in West Bengal and neighbouring Bihar, Jharkhand and Odisha states.

BRUNEI

Brunei awards EPC contract

Brunei Fertilizer Industries has awarded thyssenkrupp Industrial Solutions the engineering, procurement and construction (EPC) contract for the company's new greenfield fertilizer facility at the Sungai Liang Industrial Park. The complex, which is due for completion in 2021, will have a production capacity of 2,200 t/d of ammonia and 3,900 t/d of urea, as well as a downstream granulation plant. thyssenkrupp's scope of supply for this fertilizer complex will include the engineering, supply of equipment, erection, supervision of construction and commissioning as well as various offsite and related utility systems. The new plant project will support the government's long-term development strategy to diversify the country's economy. Peter Feldhaus, CEO of thyssenkrupp's Industrial Solutions

business area said: "We are proud to work together with Brunei Fertilizer Industries to support the country's transformation into a diversified industrial economy. Being selected to develop this lighthouse project is an important milestone for our fertilizer plant business. This major order will further strengthen our market position and growth in the Asia Pacific region."

Dato Bahrin Abdullah, Chairman of Brunei Fertilizer Industries: "We have chosen thyssenkrupp for our investment project as the company combines vast experience in engineering, procurement and construction with proven and cost-efficient fertilizer production technology, ensuring the highest environmental standards. Together, we will help accelerate the nation's economic growth in a sustainable way and expand employment opportunities for its people."

TURKMENISTAN

Urea project 80% complete

State owned Turkmenhimiva's new \$1.3 billion ammonia-urea plant at Garabogaz is 80% mechanically complete, according to the company. Construction is being carried out by 5,600 workers working for the EPC contractors Mitsubishi Corporation and Turkey's Gap Insaat. Turkmenhimiya says that emergency diesel generators and air supply units have been completed, and testing of high pressure pipelines is ongoing, and that construction of a gas supply pipeline is nearing completion. At capacity the facility will produce 1.15 million t/a of urea, with around

www.nitrogenandsvngas.com

Nitrogen+Syngas 350 | November-December 2017

one third sold domestically and the rest exported. Ammonia technology is being licensed from Haldor Topsoe, with urea technology being provided by Saipem. There is also a downstream urea granulation unit which is being licensed by Uhde Fertilizer Technology (UFT), Training of 270 operations staff is also under way. as is construction of an export terminal at Garabogaz. The plant's on-stream date is set for June 2018.

BOLIVIA

12

13

15

18

22

23

25

28

29

YPFB urea plant begins production

The new ammonia-urea complex that has been developed by state-owned Yacimientos Petrolíferos Fiscales Bolivianos (YPFB) came on-stream in September at Bulo Bulo, near Cochabamba in central Bolivia, east of La Paz, according to the company. The plant was built by Korea's Samsung at a cost of \$950 million, and will produce 650,000 t/a of urea at capacity. As well as providing for all of Bolivia's relatively modest urea requirements, which stand at around 30,000 t/a, the plant will also export urea. Brazil is the main target market, and an offtake agreement has already been signed. Other potential destinations for the urea include Argentina, Paraguay, and Peru,

GERMANY

New nitric acid compressor train design

MAN Diesel & Turbo has launched NAMAX, a new turbomachinery concept for the fertilizer industry, which the company says will raise production efficiency of nitric acid. The NAMAX concept is based around an AG-MAX1 axial air compressor. While previous designs made use of an intermediate gearbox to couple the machines in the train. MAN says that NAMAX uses a direct drive, meaning that a gearbox is not required, allowing efficiency to be boosted by several percentage points, whilst simultaneously allowing the energy input and operating costs for HNO₂ production to be decreased. NAMAX also comprises a centrifugal compressor for NOx compression a MAN steam turbine and an axial expander providing the drive power. As all four machines are sourced together, they can be matched for maximum efficiency. MAN says that it will supply a NAMAX compressor train to thyssenkrupp Industrial Solutions for use in an expansion at Grupa Azoty's nitric acid plant in Poland.

www.nitrogenandsvngas.com

SPAIN AMETEK to supply imaging

technology to Air Liquide

AMETEK Land has supplied its real-time. thermal imaging Near Infrared Borescope (NIR-B) 3XR to Air Liquide to monitor catalyst life at its Madrid plant. The NIR-B 3XR. which was launched to the industrial gas sector in 2016, is able to continuously measure reformer tube wall temperature (TWT), for furnace optimisation and moni-

toring, allowing highly accurate temperature point data to be measured, stored and trended over the lifetime of the furnace. Continuous analysis of the tubes enables more informed decisions, leading to greater plant reliability and productivity. Gonzalo Navarro, production manager at Air Liquide Ibérica de Gases, Madrid said: "Our steam methane reformers produce hydrogen and carbon dioxide industrial gases and are business critical assets. However, they are also challenging assets to operate and maintain. Our main reason for this investment is to extend tube and catalyst life - and we are already starting to see the benefits."

RUSSIA

Metafrax selects Casale for Gubakha complex

PJSC Metafrax has awarded Casale a contract for engineering, equipment supply and construction management of Metafrax's new nitrogen line, to be built at the company's existing site at Gubakha in Russia's Perm region. Casale will act as technology licensor and EPC contractor for the entire proiect, which includes: an 890 t/d (290,000 t/a) ammonia plant using Casale's A2000C technology; a 1,725 (570,000 t/a) urea plant incorporating Casale Split Flow and Full Condenser technologies; and a new 40,000 t/a melamine plant, using LEM technology. The ammonia plant will use hydrogen feed from the purge gas of the methanol plant at Gubakha, while a MHI-designed carbon dioxide recovery unit will recover 1,200 t/d of CO. from the methanol plant reformers to be used as feed for the urea plant, greatly increasing the integration and hence efficiency of the whole complex. Metafrax had previously contracted Casale to expand the methanol plant from 2,500 t/d to 3,375 t/d over the course of two decades, most recently by installing a

new partial oxidation unit section in parallel

to the existing reformers.

V. Daut, general director of Metafrax commented: "We decided to proceed in partnership with Casale because we saw a big advantage in having one single licensor for ammonia, urea and melamine, in combination with their deep knowledge of our existing methanol plant. We believe that, with its experience in all kind of revamp, Casale will realise optimal technical solutions for integrating the

new units of the complex into our existing

UKRAINE

methanol plant'

Sanctions imposed on Russian fertilizer producers

The Ukrainian economy ministry has imposed sanctions against 10 EuroChem subsidiaries, as well as other Russian-owned fertilizer suppliers, including Galaktika, Rusagrokhim, Bosnis, Agrokhimuniversal, Agrocenter-Belgorod, Agrochemcenter-Tambov, Ryazanagrokhim, Yugagrokhim, Zaraiskaya Selkhozkhimiva, Agrarnik, Tselinskagrokhimservis, Yug-Businesspartner, Tandem, Agrochemistry, Farmers Support Society and Balttreidkhim. The ministry claims that the companies are supplying nitrogen fertilizers, particularly ammonium nitrate, to the Donetsk and Lugansk regions without customs clearance - these two regions in the east of the country are currently in the hands of Russian-backed separatist rebels. The sanctions take the form of suspension of for

"It is established that these companies are supplying nitrogen fertilizers (ammonium nitrate) to the territories of Donetsk and Lugansk regions that are temporarily not controlled by the Ukrainian authorities without customs clearance via the closed checkpoints or checkpoints on the Russian-Ukrainian border forbidden by the government," the Prosecutor General's Office said. According to the ministry, the funds paid to the self-proclaimed Donetsk and Luhansk Peoples' Republics for customs clearance of mineral fertilizers were subsequently used to finance "illegal armed groups".

eign economic activities of the companies.

EuroChem, which in September transferred ownership of its Russian subsidiaries to its Swiss-based holding company. says that it "considers these restrictions to be indefensible and will shortly apply to the appropriate Ukrainian authorities for a detailed explanation of the decision." The sanctions are currently set to apply for three months from the end of October.

Nitrogen+Syngas 350 | November-December 2017

Syngas News

UNITED STATES

Permits invalidated for Kalama project

issued are thereby invalidated

and delivering safely and successfully this

new world-scale facility to operate at full

capacity," said Jonathan Lewis, CEO of

Small-scale hydrogen plant for

told local media

Amec Foster Wheeler

California

the road by 2023.

Chinese-based Northwest Innovation of potential mitigation measures. Even Works (NWIW), aiming to build a \$1.8 billion, 10.000 t/d methanol facility at Kalama, Washington State, has suffered a setback in the form of a ruling from the state Shorelines Hearings Board. The Board ruled in an appeal against the award of two environmental permits brought by three environmental groups: Columbia Riverkeeper. the Sierra Club and the Centre for Biological Diversity, in so doing agreeing

with the complainants that the Port of Kalama and Cowlitz County had failed to fully evaluate greenhouse gas emissions from what would be the world's largest methanol plant. In its summary judgment, the board wrote it was "troubled by the project's emission of greenhouse gases without further evaluation

Work begins on methanol plant relocation

US Methanol says that it has broken ground on its relocation of a methanol plant from Brazil to a brownfield site in Charleston, West Virginia operated by Dow Chemical. The plant will produce 195,000 t/a of methanol using natural gas as feedstock, and is expected to begin production in 2H 2018, according to the company. An appeal against the plant's air quality permit was recently thrown out by the West Virginia Air Ouality Board. US Methanol, owned by Czechbased investment group KKCG, also has plans to relocate a second plant, with capacity of 150,000 t/a, but as yet has no firm date for this.

Foster Wheeler awarded methanol plant contract

Engineering consultancy Amec Foster Wheeler, recently purchased by Wood Group, says that it has been awarded a \$604 million engineering, procurement and construction (EPC) contract to build a methanol plant in Louisiana. The plant to be sited at St. James Parish, will be operated by Chinese-owned Yuhuang Chemical Intl (YCI)

"Winning this contract is a further demonstration of how we are leveraging our multi-market capabilities to better serve

IRAN Japan to provide credit for Veniran methanol plant

without including all off-site sources, The long-delayed Veniran methanol proiect. a 1.65 million t/a methanol facility in the project will emit more than one million tons of greenhouse gas annually, the southern port city of Assalouyeh, looks increasing Washington's total emisto be back on again after securing up to sions by more than 1%." The decision €220-230 million of financing from Japareturns the final environmental impact nese companies, Tourai Sevved Arvanaghi, statement to Cowlitz County and the managing director of Veniran Apadana. said the Japanese finance would amount port for further analysis and the two to around half of the costs of the new environmental nermits previously methanol plant, which is estimated to cost In response, NWIW says that it plans \$550 million. The companies will provide to evaluate its next possible steps with a so-called usance (deferred payment) letter of credit, which typically includes a the project. "We understand that the environmental policy in this state is evolvdate of repayment up to six months from the date the letter of credit is issued, making and we look forward to continuing our collaboration with regulators, stakeholding it a useful financial tool for meeting ers, and environmental and business short-term investments. Originally the fruit leaders." NWIW president Vee Godley of a now-defunct collaboration between the governments of Venezuela and Iran which aimed to build two methanol plants. one in each country, Veniran Apadana is our clients, extend our presence in highnow owned by the semi-private Persian growth areas, such as the chemicals mar-Gulf Petrochemical Industries Company ket. and contribute to the growth of our (PGPIC), Iran's largest petrochemical comorder book. We look forward to working pany, 60% owned by the state, including a with YCI to meet the project's challenges. 20% direct share from the National Petro-

SPAIN

Air Liquide commended for 3D printed hydrogen reformer

chemical Company (NPC).

The European Federation of Chemical H2 Renewables is looking to build a small Engineering (EFCE) has awarded its 2017 hydrogen plant at Stillwater Business Process Intensification Award for Indus-Park in the city of Redding, California, in trial Innovation to an innovative project order to supply hydrogen-fuelled vehicles. by Air Liquide involving the development While H2 Renewables is generally looking of a 3D printed reactor used to increase at hydrogen production from electrolysis, the efficiency of hydrogen production. The local media reports suggest that this reactor is a 3D printed milli-structured plant will actually use steam reforming heat exchanger reactor designed speof methane to produce 8.6 t/d of hydrocifically for the production of hydrogen by gen. At a cost of \$22 million, the plant is steam reforming natural gas. The reactor aimed to be up and running by mid-2019. optimises the hydrogen-making process H2 Renewables is reportedly looking to by reusing the heat used in the initial build the plant then sell ownership on to excess steam production and increasing "a Pennsylvania energy company". Grants the heat transfer between the hot process from the California Energy Commission streams. According to Air Liquide, reusare available in California to build a neting heat has helped the reactor reduce work of 100 hydrogen fuelling plants. operating costs by 20% and CO2 emis-Although there are only about 1,600 sions by 12%. Air Liquide began work on hydrogen fuel cell vehicles currently operthe 3D printed reactor in 2015, and has ating in the state, this is expected to rise successfully tested the device at its Paris to 37,400 hydrogen fuel-cell vehicles on Saclay research centre (where the reactor was operational for over 3,000 hours).

www.nitrogenandsvngas.com

\checkmark

CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

NITROGEN+SYNGAS **NOVEMBER-DECEMBER 2017**

BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

The company is now building an industrial pilot plant (expected to be up and running by late 2018), and says commercial applications for its 3D printed reactor technology could be available as soon as 2020. It is confident that the reactor technology will positively impact a number of hydrogen-using fields, including oil and gas, floating liquefied natural gas, and even small scale hydrogen microgeneration.

CHINA

10

12

13

15

18

23

25

27

28

29

30

China plans massive industrial relocation

China plans to complete a massive \$120 billion relocation of chemical plants away from major cities and into designated industrial parks by 2025, according to a document issued in September by the country's State Council. For small- and medium-sized plants, the relocation must begin by 2018 and be complete by the end of 2020, while larger plants must begin the process by 2020 and complete the relocation by the end of 2025. These plants can also be re-engineered to produce non-toxic products, or permanently close if relocation is not possible. Local governments are being required to submit detailed work plans, including company lists and timelines for relocation before the end of this year.

The move is an attempt to tackle chronic pollution concerns. Since 2014, provincial governments have been submitting to the central government a list of chemical plants up for relocation and/or re-engineering, and approvals have ceased for projects in cities, requiring that all new projects be located in industrial parks. So far however, only around 20% of these planned relocations have actually been implemented. A major sticking point has been the sources of funding for the relocation projects. Government support for the projects has typically been than 10% of the total capital required and has come in the form of land, low interest rate loans and tax breaks.

Air Liquide to supply ASUs for MTO plant

Air Liquide Engineering & Construction has signed a supply contract with Yulin Energy and Chemical Corporation, a subsidiary of the Shaanxi Yanchang Petroleum Group, to design and build two large air separation units (ASU) with an oxygen capacity of 1.800 t/d each. The

ASUs will provide oxygen and nitrogen for the customer's mega methanol-to-olefin project at the Jingbian Energy & Chemical Integration Industrial Park, Shaanxi Province. Air Liquide has a longstanding partnership with Yanchang Group, the fourth largest energy company in China. In the 2014, Air Liquide Engineering and Construction delivered two 1,440 t/d ASUs to the Yanchang-Jingbian Phase I Project. Two additional ASUs of 1,400 t/d each are currently under construction to supply oxygen "over the fence" to Yanchang for

BOTSWANA

its project Yanan.

Tender issues for CTL project

State-owned Botswana Oil Ltd (BOL) has closed a tender for a 20.000 bbl/d coal to liquid (CTL) plant for fuel production. attracting 11 bidders. BOL now anticipates a two month evaluation process, followed by negotiations and contract signing in December 2017. The \$4 billion requires up-front investment by the bidder, with the Botswanan government acting as a guaranteed off-taker. Botswana hopes that it will ultimately be able to domestically produce up to 75% of the 1.2 billion litres of gasoline that the country consumes every year. Botswana is seeking to diversify its economy away from diamonds, its biggest export, and reduce its reliance on fuel from neighbouring South Africa, which supplies more than 90% of demand, while taking greater advantage of its more than 210 bil-

lion tonnes of estimated coal reserves.

INDIA

Construction begins on Assam methanol plant

Construction work has begun on the 500 t/d methanol expansion project at Assam Petrochemicals Ltd at Namrup in Assam state, following a ground-breaking ceremony inaugurated by Assam chairman Jagadish Bhuyan in the presence of local member of the legislative Naren Sonowal, vice chairman Bikul Deka and managing director Ratul Bordoloi. The project's cost is put at \$210 million. Speaking at

the ceremony, Sonowal said that the new plant would herald a new beginning for the industrial sector of Assam State and would lead to the setting up of several ancillary industries using the increased methanol production from the new plant, including a 200 t/d formaldehvde plant.

AUSTRALIA

South Australia launches tender for hydrogen plant, buses

The South Australian government has called for tenders for hydrogen infrastructure proposals, and for the supply of hydrogen-fuelled buses, as part of its plan to transform the state into a zero carbon "hydrogen economy," based on wind and solar power - the state currently produces 50% of its energy from wind and solar. The tenders are part of the state government's Hydrogen Roadmap, launched in September under its \$150 million Renewable Technology Fund. The government is also seeking to trial at least six hydrogen cell buses in the Adelaide Metro fleet, and is calling for proposals to supply those, along with necessary refuelling and hydrogen fuel production infrastructure

GERMANY

Shell looking to renewable hydrogen for refining

Royal Dutch Shell, together with ITM Power, has announced that it will build a 10 MW electrolyser at the Wesseling refinery site within the Rheinland Refinery Complex in Germany, in order to supply hydrogen to its refining activities. This would be the largest unit of its kind in Germany and the world's largest PEM (polymer electrolyte membrane) electrolyser. Surplus hydrogen could also be used to help balance energy demands from the electricity grid or be sold to customers for their own uses. The refinery currently consumes approximately 180,000 t/a of hydrogen, which is generated as a byproduct of refinery process streams or via natural gas steam reforming

Shell's partner ITM Power is pivoting from building hydrogen fuelling stations for cars to electrolysers which will turn electricity from the grid to hydrogen for industrial uses or even grid energy storage.

ITM Power CEO. Dr Graham Coolev. said: "Decarbonising hydrogen production in the chemical and refining industries worldwide is potentially a very large market. This pioneering project with Shell aims to demonstrate what can be achieved using our industrial scale electrolysers which can also use low cost renewable energy and help to balance electricity grids."

People

Wood Group says that it has completed the acquisition of Amec Foster Wheeler. Robin Watson, CEO of Wood Group commented: "This transformational acquisition creates a global leader in the delivery of

project, engineering and technical services to energy and industrial markets. We become a business of significant scale and enhanced capability, delivering services across a broader range of geographies and sectors... we expect to deliver significant cost synergies and incremental revenue synergies in a less cyclical business which retains a predominantly reimbursable, asset light model with a balanced risk appetite." Following the acquisition, lan McHoul, Linda Adamany and Roy A

Franklin have been appointed to the Wood Group Board as non-executive directors. Gerhard Mestl. Head of Oxidation Catalysts at Clariant, has received the 2017 Applied Catalysis Award from the European Federation of Catalysis Societies (EFCATS). The award was presented to Gerhard Mestl on Wednesday, 30th August at the Europa-Cat XIII conference in Florence. The recipi-

ent of the EFCATS Applied Catalysis Award

is selected by a jury of prominent scientists. According to the organization, the Award aims to acknowledge "individual contributions, which demonstrate excellence, scientific novelty, technical achievements in development and scale-up, interdisciplinary

Calendar 2017/18

NOVEMBER 2017

14-16

Conference

12th GPCA Forum, DUBAI, UAE Contact: Jill Raine. Fertilizer Outlook and Technology Registration Team Leader Telephone: +44 20 8652 3233 NEW ORLEANS, Louisiana, USA Email: GPCA.registrations@rbi.co.uk Contact: Valerie Sutton, The Fertilizer

FEBRUARY 2018 Instutite 425 Third Street S.W. Suite 950 Washington D.C. 20024, USA Nitrogen+Syngas 2018.

Tel: +1 202 962 0490 Email: vsutton@tfi.org Web: www.tfi.org/fotc

Iranian Nitrogen+Syngas Conference, TEHRAN, Iran Contact: CRU Events, Chancery House, 53-64 Chancery Lane, London WC2A 1QS, UK Tel: +44 (0) 20 7903 2444 Fax: +44 (0) 20 7903 2172 Email: conferences@crugroup.com

Nitrogen+Syngas 350 | November-December 2017

teamwork between scientists and engineers, and clearly show emphasis on actual or potential commercial application". The Applied Catalysis Award is sponsored by the multinational petroleum company BP.

Mestl's award was for his work in selective oxidation. Together with his R&D team at Clariant, Mestl has succeeded in developing high-performance process catalysts that significantly enhance efficiency and sustainability in the production of intermediate and specialty chemicals, such as phthalic anhydride (PHTHALIMAX®), maleic anhydride (SynDane®) and vinyl-acetate monomer (VAMax®).

Prof. Robert Schloegl, Director at the Fritz Haber Institute of the Max Planck Society, stated, "Gerhard unites academic interest and curiosity with the practical sense and perseverance needed in industrial catalysis research. I wish him all the joy coming with such a prestigious award." Marvin Estenfelder, Head of R&D at Clariant's Catalysts Business Unit, also offered his congratulations: "The EFCATS Award is well-deserved recognition for the valuable contribution of Gerhard and his team to a number of exceptional innovations."

CF Industries Holdings has announced that Susan L. Menzel will be joining CF as senior vice president, human resources on October 5th, 2017, Menzel will be responsible for human resources strategy and

GOTHENBURG, Sweden

Tel: +44 (0) 20 7903 2444

Fax: +44 (0) 20 7903 2172

Email: conferences@crugroup.com

IFA Production and International Trade

Meeting, BUENOS ARIES, Argentina

28 rue Marbeuf, 75008 Paris, France

Contact: IFA Conference Service.

Contact: CRU Events

MARCH

Tel: +33 1 53 93 05 00 Email: ifa@fertilizer.org

APRIL

IFA Global Technical Symposium, MADRID, Spain Contact: IFA Conference Service. 28 rue Marbeuf, 75008 Paris, France Tel: +33 1 53 93 05 00 Email: ifa@fertilizer.org

SynGas Association Meeting 2018, TULSA, Oklahoma, USA Contact: SynGas Association Tel: +1 225 922 5000 Web: www.syngasassociation.com

JUNE

85th IFA Annual Conference. BERLIN, Germany Contact: IFA Conference Service Tel: +33 1 53 93 05 00 Email: ifa@fertilizer.org

www.nitrogenandsvngas.com



Susan L. Menzel

management for the company and serve as a member of the senior leadership team. reporting to Tony Will, president and chief executive officer. CF Industries Holdings, Inc. "Sue's proven track record of providing strategic business and human capital leadership, along with her experience partnering with senior executives and boards of directors to improve talent management and maximize employee engagement, will serve CF and our employees well," said Will. "We look forward to having her help

> us drive continuous improvement both within the HR function and across the whole company."



NOVEMBER-DECEMBER 2017

 \checkmark

What's in issue 350

COVER FEATURE 3

Fertilizers from

COVER FEATURE 4

debottlenecking

Nitrate plant

gasification

CONTENTS

BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

Nitrogen+Syngas 350 | November-December 2017



Plant Manager+

Problem No. 45 Effect on reactor liner in case of reactor hold up

In the case of a failure in a urea plant, when the problem is expected to be solved within a short period, the high pressure synthesis section is typically blocked in (referred to in this article as reactor hold up). All input and output streams are closed and the synthesis section remains partly filled with a and; 3) an explosive gas mixture could occur as hydrogen and solution consisting of ammonia, CO₂, water, ammonium carba-

mate and of course urea. Several risks can occur during this blocked in situation: 1) as the temperature slowly reduces crystallisation could occur; 2) active corrosion could start as no fresh oxygen is supplied to the synthesis during blocking in oxygen are present.



Sandeep Gochar of GNFC in India initiates a discussion on this topic: I am working in a Saipem technology urea plant. I would like to know what effect keeping the reactor in hold up conditions after a shutdown will have on the reactor liner. Usually Saipem recommends draining the reactor if the shutdown is longer than 48 hours.

Prem Baboo of NFL India replies: Generally, the new practice in our plant is to have reactor hold up solution for no more than 48 hours. The reactor must be drained within 48 hours. Some corrosion was observed due to the low CO₂ purity (98.0 vol-% or less). Secondly the ammonia feed is not pure; it has some oil contents including some sulphur. Chlorine is also present in the passivation air. Our practice is as follows:

- feed liquid ammonia every 15 hours:
- drain the reactor within 48 hours;
- ensure a proper NH₂/CO₂ ratio;

18

21

22

23

28

29

30

- ensure purity of CO₂ (reduce hydrogen and organic matter slipping from the CO, removal section):
- during start-up introduce NH₃ feed 10-15 min prior to CO₂ feed.

Sandeep asks for some clarifications: Feeding liquid ammonia every 15 hours is something new for us but we will definitely look into it. Suppose we have reactor hold up for 48 hours, how does it affect the reactor liner thickness? One more question, which area (bottom, middle, top) of the reactor liner is more prone to thinning in the case of hold up or is the affect uniform throughout the reactor?

Prem replies to Sandeep: The top part of the reactor lining is more prone to thinning. If you feed ammonia then the reduction in thickness at the bottom of the reactor liner is always less than at the top. The solution must be drained within 48 hours. Do not exceed 48 hours. If you have a planned shutdown, first stop the CO₂ feed and then after 8-10 minutes stop the ammonia feed.

Mark Brouwer of UreaKnowHow.com in the Netherlands asks

Prem some additional questions: What is the best practice during blocking in of a Saipem synthesis with regard to the following: Position of MP vent valve (to avoid accumulation of hydrogen);

- Steam pressure on stripper:
- Do you monitor the temperature in the reactor to assure no CO₂ leaks in?
- When you add ammonia every 15 hours, do you reduce the level in the HP level tank? As the ammonia enters the reactor via the HP ejector, is there a risk that the HP level tank will be empty?
- How much time should expire after start up before another blocking in of 48 hours is allowed?

Prem replies to Mark:

 Whenever there is a plant shutdown the MP vent is in auto mode, the excess pressure caused by inerts $(H_2/CH_4/N_2/O_2/$ Ar and some ammonia, etc.) is released and then the valve closes automatically, i.e. during shutdown the MP vent valve is in closed condition (after the hydrogen and all inerts have been vented out).

• During shutdown the steam pressure is zero on the stripper shell side

UREAKNOWHOW.COM ROUND TABLE

- Yes, the temperature of the reactor must be more than 126°C and is generally run at about 140-165°C.
- Yes, the level in the HP level tank is reduced. If there is no ammonia left, take it from ammonia storage. If it is unavailable for any reason (shutdown of equipment etc.) it is not a problem. We try to drain the reactor within 40 hours for equipment health. There is no harm in draining out the HP loop solution, the effluent (urea, ammonia and CO₂) will be recovered after shutdown. Draining means no effluent will drain out into the open. It should be collected in vessels (ammonium carbonate, urea solution tank etc.). These tanks are at atmospheric pressure and low temperature so there is less corrosion. Equipment health is always better than production loss.
- Another blocking in of 48 hours is permitted once the reactor is receiving feed and all of the solution has been replaced with fresh solution and with passivation air.

Mark asks for some more information: Have you ever experienced passing of the CO₂ valves resulting in CO₂ entering the reactor during blocking in? This would lead to higher temperatures and possibly active corrosion.

What is the reason for adding some ammonia every 15 hours? Does it reduce the risk of corrosion or crystallisation?

Prem replies: As regards CO₂ leakage, there are two feed valves: one is a motor operated angle valve (MOV) and the other is a pneumatic valve also angle (needle valve), so there is less chance of leakage

When the feed is stopped, stop the CO₂ compressor immediately and there will be no risk of leakage due to the compressor tripping.

If the compressor is operating, the discharge pressure may be reduced to less than the system pressure (reactor pressure) so that there is no risk of leaking.

It is important that the operator stops the CO₂ feed first and then the ammonia to prevent CO₂ leaks.

Ammonia addition reduces the risks of both corrosion and crystallisation.

reactor temperature not being allowed to go below 126°C.

- risk of crystallisation:
- up again.

This series of discussions is compiled from a selection nitric acid and other fertilizers.



In search of top performance



OTHER ANIVI DIVISIONS:

GRINDING AND CLASSIFICATION AIR AND GASES MODULAR SYSTEMS



ANIVI INGENIERIA.S.A. Avda, Chorierri, 8 48180 Loiu (SPAIN) Tel: +34 94 453 19 00 info@anivi.com www.anivi.com



CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

TER SALES	
SISTANCE	
GINEERING	
RECTION &	
IPERVISION	
VAMPINGS	
	NO\



ITROGEN+SYNGAS

EMBER-DECEMBER 2017

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com



- Mark replies to Sandeep: Two reasons are given:
- to reduce the temperature shock when the plant is started

of round table topics discussed on the UreaKnowHow. com website. UreaKnowHow.com promotes the exchange of technical information to improve the performance and safety of urea plants. A wide range of round table discussions take place in the field of process design, operations, mechanical issues, maintenance, inspection, safety, environmental concerns, and product quality for urea, ammonia.



Power to ammonia

Making ammonia from hydrogen generated by electrolysis of water has a long history, and today, coupled with renewable electricity, offers the prospect of a carbon neutral source of ammonia. But can the economics possibly stack up?

he history of producing ammonia via hydrogen from electrolysed water is almost as old as the ammonia industry itself. While hydrogen was available from coal gasification, as was used in BASF's first ammonia plant at Oppau in 1913, it required a secondary water-gas shift reaction to generate sufficient hydrogen for the process. Other pioneers quickly looked into using electrolysis to split water into hydrogen and oxygen. In 1919, Luigi Casale built the first electrolysis-based ammonia plant at Terni in Italy using his own high-pressure ammonia synthesis process, followed soon after by Norsk Hydro at Rjukan in Norway in 1927, after Hydro signed a licensing agreement with IG Farben for the Haber-Bosch ammonia process.

15

18

23

28

Continuing improvements to the syngas generation process gradually brought the cost of production down, and this proved even more decisive once steam reforming of methane began to become the standard way of generating syngas. Nevertheless. a few electrolysis-based ammonia plants were subsequently constructed in the 1940s and 50s near major hydro-electric dam projects, such as at Aswan in Egypt, or the Sebakwe Dam in Zimbabwe. Chile, Iceland, Peru and Canada also all had at one time or another electrolysis-based ammonia plants. The major drawback, however, was the cost of production. It

takes around 10-12 megawatt hours (MWh) of electricity to produce enough hydrogen to make a tonne of ammonia. At an average 2017 cost of around \$70/ MWh in the United States, this would translate to \$840/tonne of ammonia before any other costs were taken into account. Even though hydroelectric generation tends to be cheaper, it would still require \$550 of hydroelectricity to produce a tonne of ammonia in the US. Compare this to around \$75-100/tonne of ammonia in terms of natural gas cost at prevailing US gas prices, and it can be seen why electrical generation of hydrogen fell out of favour. Globally, only the Aswan plant in Egypt is still operational; the Rjukan ammonia plant in Norway closed in 1991, Iceland's hydroelectric ammonia plant closed in 2004, and the Sable Chemicals facility in Zimbabwe finally ceased production in 2015 and the company switched to

A new paradigm?

buying ammonia from South Africa.

On the face of it, then, the future for ammonia from electrolysis seems bleak. However, the growing interest in generating power from renewable sources may yet throw it a lifeline. Of course, hydroelectricity is a renewable power source, and were there to be a carbon cost to ammonia pro-

duction that might narrow a small amount of the gap between electrolysis and fossil fuel-derived hydrogen. Nevertheless, this would still leave electrolysis at a significant cost disadvantage and could not promote its use without major subsidy. However, large scale installation of solar power and wind turbines is leading to a new issue for electricity producers - the fact that power is not always produced when needed, and that there can be large excesses of power being generated at times of low demand. Were this to be used to produce hydrogen via electrolysis, and thence downstream ammonia, it could be used as a way of 'storing' renewable power in a way which is far cheaper than present battery technology. Storing ammonia compared to hydrogen is more attractive because pressurised storage (at ambient temperatures) of limited volumes of NH₂ can be done at around 10 bar while the equivalent pressures required for H₂ are 350 bar or higher to achieve a reasonable - but still lower - volumetric energy density. Large scale cooled storage (at atmospheric pressure) of NH₂ can be done at -33°C, while it would

P2A

A recent study in the Netherlands looked at the issues surrounding 'power to ammonia' (P2A). Funded by the Dutch Ministry of Economic Affairs, it was organised by the Institute for Sustainable Process Technology (ISPT) in conjunction with Stedin Infradiensten, Nuon, ECN, Technical University Delft, University Twente, Proton Ventures, OCI Nitrogen, CE Delft and AkzoNobel, The

require a temperature of -254°C for H₂.



We know our way around engineering

Think about thousands of highly skilled professionals operating in the oil & gas processing, petrochemicals and fertilizer industries: this is Maire Tecnimont Group, an engineering and construction leader dedicated to providing consumers at the end of the value chain with energy in its different forms. We create value with innovative products for a countless number of industrial applications embedded in everyday life.

40 COUNTRIES **50 OPERATING COMPANIES**







Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567

> Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

COVER FEATURE 4

debottlenecking

NITROGEN+SYNGAS

NOVEMBER-DECEMBER 2017

BCInsight

Nitrate plant

www.nitrogenandsyngas.com

www.mairetecnimont.com

17

15

18

23

25

28

29

30

purpose of the study, which concluded in February 2017, was to "investigate both technologically and economically under what conditions NH₂ can be produced using renewable electricity; can be used to store electricity; and can be used as a fuel for an electricity production facility. The project studied three cases:

- (i) Electrochemical production, storage and use of NH₂ in a rural setting (Goeree-Overflakkee), avoiding grid modification costs and allowing local production of CO₂-free NH₂.
- (ii) Use of NH_3 as a CO_2 -neutral fuel in the highly efficient Nuon Magnum gas turbine combined cycle (CCGT) power plant at Eemshaven.
- (iii) Using electrochemical production of NH₂ at OCI Nitrogen to replace (some of) the current, natural gas-based production.

Using ammonia as electricity storage

The Dutch island of Goeree-Overflakkee has a large concentration of renewable electricity production from wind and solar sources. and a tidal facility is also under consideration. This leads to a net electricity capacity of up to 300 MWe, far exceeding electricity demand on the island, rated at a maximum of 30 MWe at peak. Further investment in the electricity grid is necessary to accommodate the increase in renewable electricity production, to a total of €50 million. Producing ammonia from surplus power was investigated as a way of avoiding this cost, with the ammonia subsequently being transported by truck to existing storage tanks at Rotterdam harbour

Three alternatives were considered; (a) producing ammonia with electricity from the new 25 MW tidal power facility at Brouwersdam, (b), direct NH₂ production at the Middelharnis grid substation, where power from various wind and solar facilities meet, and more power can be drawn from the national grid, and (c) production of ammonia at a standalone wind park. This has the disadvantage of a more fluctuating and less predictable supply of power.

Overall, the study found that there was no "positive business case" for the production of ammonia from electricity at present. The case where NH₃ is produced directly at the grid substation in Middelharnis, with a capacity of 40,000 t/a from small, modular units, appeared most promising. Other alternatives considered were less interesting because the intermittent production of renewable electricity would mean lower utilisation of the installed assets and the

Table 1: Comparison of ammonia as an electricity storage technology

rechnology	Physical properties			Economics		
	Pressure (bar)	Temp (°C)	Density (GJ/m³)	Relative CAPEX	Loss (%, 6 mo)	
Liquid H ₂	ambient	-254	4.8	++	5.5	
Pressurized H ₂	700	ambient	2.8	N/A	-	
MCH*	ambient	ambient	1.7	+++	-	
H18-LOHC**	ambient	ambient	2.0	+++	-	
Iron sponge	ambient	ambient	6.5	N/A	-	
Methane	ambient	-163	11.4	0	3.0	
Methanol	ambient	ambient	8.2	0	-	
Ammonia	ambient	-33	6.8	0	0.6	

* methylcyclohexane ** liquid organic hydrogen carrier

costs for electrolysers going forward, and

for CO₂-based production.

Source: Institute for Sustainable Process Technology, Power to Ammonia Final Report



need for larger and costly storage facilities energy storage. These are shown in Figure for H₂ in order to operate the Haber-Bosch 1 with a comparison with other chemi process section at its minimum capacity cal methods in Table 1, and indicate that of 25%. However, different scenarios for ammonia, as well as other chemical storage methods such as methanol is a viable future electricity prices have shown a great variety in the outcome for the NH₂ price, option for large scale storage. with potential upsides coming from lower

Burning ammonia for power

possible subsidy for 'zero emission' ferti-The business case was investigated for lizer production/potential future penalties production of NH₂ from low CO₂ sources as a fuel for the Magnum CCGT power The project compared electricity storplant. The key issue with the conversion age as ammonia with other ways of storing of ammonia to power is the combustion; electricity, using batteries or capacitors, or little is known about ammonia combustion mechanical options such as flywheels, liqin spite of some work performed on recipuid air energy storage or compressed air rocal engines and direct combustion in gas



www.nitrogenandsyngas.com

For more information and to book your place, visit www.nitrogensyngas.com

www.bcinsightsearch.com



What's in issue 350

CONTENTS

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking



BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

turbines. Turbine suppliers consulted were concerned about the low flame speed and hence larger flame size and the risk of high NOx-formation due to the existence of nitrogen containing radicals during the combustion. In theory these could be mitigated by designing a new combustor in which a rich mixture is combusted resulting in low nitric oxide (NOx) formation followed by adding secondary air to create a lean continued combustion. However, such development is not part of the current research and development programs of OEMs.

Ammonia can also be 'cracked' back to hydrogen and nitrogen by heating it to 800-900C. This leaves trace ammonia in the process gas but current ammonia cracker sizes of 10 t/h would need to be scaled up to 200 t/h, adding perhaps a decade to development times. Nevertheless, this seems the most promising option. It was also considered whether ammonia could be used as an intermediate way of storing power at the plant, a so-called 'power-to-power' option. The efficiency of this was only 25-40%, depending on the electrolyser technology, compared to battery storage of 85-90%, but it could handle much larger volumes.

12

14

15

18

20

23

25

28

29

The study concluded that using cracked NH₂ for combustion provides integration options with other H₂ consumers. Ammonia produced from natural gas including carbon capture and storage (CCS) or NH₃ produced from remote continuously available renewable electricity (e.g. hydro or geothermal) shows reasonable costs. This means that the costs of electricity produced from this NH_a are lower than €150/MWh, making it viable for a SDE+ type subsidy regime. While ammonia can be used to store locally excess renewable electricity at times when prices are low, the economic feasibility is only positive if the investment cost for the electrolysers decreases drastically in combination with high run times for the plant and a positive business model for such storage. The main cost driver for a P2A plant are the electrolysers, being more than 60% of the total CAPEX. A target for cost reduction is 70% of the current base price of €1,000/ kW. Nuon aims for co-firing cracked NH₂ as a fuel in the Eemshaven CCGT power plant in 2021 and for a full conversion in 2026

OCI Nitrogen

A third business case has been developed for a small scale (20,000 t/a) pilot P2A plant at OCI Nitrogen, either at their site in Geleen or in Europoort. At both sites the infrastructure for chemical processes and

www.nitrogenandsvngas.com

NH₂ is already present, reducing the investment in utilities and handling as well as reducing the lead time, costs and complexity of the permits. In their submission to the study, OCI noted that ammonia production requires capital intensive installations and large energy flows. For electrochemicalbased NH₃ production the investments are even higher. In order to achieve the lowest possible price, energy should be cheap and the installation should run for a large number of hours, and the availability of low cost electricity during a large percentage of the time will be a challenge.

The investment cost for such a plant in the order of €30 million, based on an estimate by Proton Ventures. Electricity consumption and other variable costs (demineralised water, air etc are mainly energy driven) will be equivalent to 10.5 MWh/t ammonia. Assuming relatively continuous operation (>5,000 hours per year), the cost of production at current electricity prices would be around €1,000/tonne ammonia, far in excess of current prevailing market prices, but in 2030 in a high renewable energy scenario case the price differences are smaller, with production costs dropping to around €500/tonne (\$585/t). Even this is still higher than prevailing ammonia market prices of around \$300/t, but OCI believes that with further optimisation of the operational hours the break-even point

The company notes in the report that it has reached the following conclusions from the study;

could possibly be reached.

 If the investment cost, mainly in the electrolysers, could be reduced significantly and/or the pricing of renewable NH₂ is significantly higher and/or the cost for CO₂ emissions are higher, the electrification route could be profitable before the year 2030. Innovations in electrolyser markets such as the battolyser appear to have a great potential. Other ways to increase profitability could be to act on both the day-ahead-market and imbalance market for electricity, and to include avoided investment (e.g. in power grid) and to find subsidy schemes (like SDE+/

EIA) or attractive financing models. • In order to reduce the CO₂ footprint of electrochemically produced NH_a, compared to conventional NH₃, the electricity has to come from a CO2-free source. When using CO₂ electricity from non-renewable energy sources the CO₂ footprint is actually higher due to the efficiency loss when producing electricity. Per ton NH₂ produced by renewable electricity 1.8 tonnes of CO₂ are avoided compared to natural gas based steam reforming, but if 'grey' electricity based on the Dutch fuel mix is used, the CO₂ emissions are three times higher compared to the one for SMR.

 Although the ultimate goal is to eliminate CO₂ emissions at both electricity and NH₂ production, for traditional NH₂ suppliers it is a logical path to expect that at first the huge existing NH₂ volumes will be decarbonised before using the ammonia for electricity production in gas fired power stations. The natural gas that is no longer used for NH₃ production can be used more efficiently to produce electricity when renewable energy is in short supply. OCI expects that usage of NH₂ on a smaller scale as a fuel for power stations, to develop sooner. This is driven by the market (consumers are willing to pay for CO2-free electricity) and electricity suppliers looking for ways to implement this technology on a small scale.

Overall conclusions

The report says that P2A has long term potential to contribute substantially to CO2 reduction targets, as it can offer flexibility for the energy system, play an important role in substituting fossil based NH₂ and allows for smart choices with regard to avoiding high capacity investments in the electricity grid. However, the production of green ammonia from renewable electricity in the Netherlands is not economically attractive in the short term due to limited availability of cheap renewable electricity resulting in a limited number of operating hours in combination with high investment costs, mainly determined by the electrolysers for the production of H₂. Attractiveness might be achieved if the specific investment costs for electrolysers were to be reduced by about 70%.

As prices of electricity generated from solar energy are dropping very rapidly, PV generated electricity has become a potentially interesting source for NH₃ production based on renewable sources. In 2016 prices have dropped by approximately 50% (from \$48/MWh to \$24/MWh according to the recent record bid by Jinkosolar/Marubeni for a large scale Abu Dhabi project).

Kopernikus – P2X

In Germany, a similar research programme forms part of the so-called Kopernikus initiative. Launched by the Federal Ministry of Education and Research (BMBF), it aims

Nitrogen+Syngas 350 | November-December 2017



AMMONIA NITRATES & PHOSPHATES UREA MELAMINE METHANOL SYNGAS

PROPRIETARY TECHNOLOGY LICENSING



1.125 1 10 10 1 2 Th

to "stimulate comprehensive and integrative research on the energy transition in order to make the current system in a safe, affordable, and clean way fit for the future". It has four components: ENSURE, which addresses new grid structures to transport and supply renewable energy in a reliable and flexible way; P2X, which focuses on options to store energy in gaseous, substantial, or liquid form; SynErgle, looking at technologies for adapting industrial processes to the new energy supply system; and the ENavi project, analysing the interaction of the power, heat, and mobility sectors.

P2X project partners include: Clariant, RWTH Aachen University, Forschungszentrum Jülich, Friedrich-Alexander University Erlangen/Nuremberg, Karlsruhe Institute of Technology, the Fraunhofer Institute, Leibniz-Forschungsverbund Energiewende, Areva H2Gen GmbH, Hydrogenious Technologies GmbH, and thyssenkrupp Industrial Solutions AG. At the moment it is not looking at ammonia, however, but rather using renewable hydrogen in the manufacture of Fischer-Tropsch liquids, methanation, gasoline via renewable methanol, and syngas fermentation to long-chain alcohols. The programme runs form 2016-2019.

ARPA-e REFUEL

13

14

15

18

20

22

23

25

28

29

30

In the US, work on similar projects is being conducted under the auspices of the Advanced Research Projects Agency – Energy (ARPA-e) via its Renewable Energy to Fuels through Utilisation of Energy-dense Liquids (REFUEL) program. ARPA-e says that this seeks to develop "scalable technologies for converting electrical energy from renewable sources into energy-dense carbon-neutral liquid fuels (CNLFs) and back into electricity or hydrogen on demand. REFUEL projects will accelerate the shift to domestically produced transportation fuels, improving American economic and energy security and reducing energy emissions."

Real world projects

Real world applications have so far been very small scale. In Iowa, a scientist from the Jet Propulsion Laboratory (JPL) developed a renewables to ammonia system at his late father's farm. The Raphael Schmuecker Memorial Solar-Hydrogen System began by installing an electrolyser to work off solar power to run a hydrogen-fuelled tractor, but in 2013 also began producing 85 kg/year of ammonia for use on the

www.nitrogenandsvngas.com

fields. Ultimately it aims to scale up to run the entire farm and generate sufficient ammonia fertilizer to cover its 300 acres (2.0 t/a) by using solar energy.

But a much more ambitious project is now under way in Australia, where Yara is finishing a feasibility study on building a demonstration plant to produce ammonia using solar power in Western Australia. The company already operates a gas-based ammonia plant at Pilbara. Once the feasibility study is complete, Yara said at a local conference in Pilbara that it hopes to move to engineering and design and begin con-

struction during 2018, with a targeted completion date and start-up time of 2019. The first stage will be a 2.5 MW demonstrator plant at the existing Pilbara site, producing 66 t/a of ammonia, which Yara says it hopes will gain it experience with the process. However, the next stage is for a scaleup to hundreds of megawatts of solar power, generating 10,000 t/a or so of ammonia, and Yara says that this "could grow to a full replacement of our current natural gas consumption by producing hydrogen with a solar field ... or even a step further" - the third stage would be a 4-20 GW solar array, generating up to 500,000 t/a of ammonia, and a potential fourth stage would be multiple plants at this scale, with the ammonia not just being used for fertilizer but also for fuel or as a hydrogen carrier. Australia's Commonwealth Scientific and Industrial Research Organisation (CSIRO) is also conducting research into a catalytic membrane which will split ammonia back into nitrogen and hydrogen and allow the ammonia generated by solar power to be used as a hydrogen transport vehicle. While metal hydrides (which have been suggested as a method for storing and transporting hydrogen) carry only 3% of their weight as hydrogen, ammonia is 18% hydrogen by weight. The project partners believe that this might offer a way of linking areas with a high density of solar energy such as Australia's western deserts with energy consuming states like Korea and Japan which have only half the intensity for of solar light and far less space to develop large solar arrays.

The future is ammonia?

So is ammonia derived from renewable hydrogen the energy carrier of the future? Many people seem to think so, but various extremely large caveats need to be stated at this point. Ammonia is often cited as a 'clean-burning' fuel, generating in theory

only water and nitrogen, but in fact as any nitric acid plant operator will tell you, it actually tends to generate large quantities of nitrogen oxides. For this reason the Dutch study cited above effectively ruled out ammonia as a power plant fuel. Secondly, ammonia is toxic, and its transport and storage is under increasing scrutiny, especially in the United States. It is one thing to ship it in an LNG carrier from Australia to Korea or Japan, but quite another to imagine any kind of ammonia distribution.

The cost angle of generating hydrogen from electrolysis continues to be the real bugbear of the process, with figures of \$850-1150/tonne ammonia at current wholesale electricity prices, in addition to the large capital expenditure of the electrolysers. There are expectations that the cost of electrolysers will come down as they become more widespread and new technologies mature, and the cost of electricity is likewise likely to fall as renewable power becomes more widespread. Even so, a projected 2030 cost of \$500/t means that ammonia will still be more expensive from renewable sources than from natural gas or coal gasification, albeit not much more so at the top of the current ammonia price cycle. But even if the economics can potentially be made to stack up, there are other drawbacks. One of the advantages cited is that the hydrogen can be generated during times of surplus production from renewables and used as a way of 'storing' that energy. Unfortunately, an intermittent source of hydrogen is an incredibly inefficient way of running an ammonia plant, so considerable hydrogen storage capacity could be needed to ensure a constant supply to the ammonia synthesis section. And if the ammonia is then to be converted back into hydrogen, a lot of work needs to be done on the 'cracking' of ammonia back to nitrogen and hydrogen - it is no coincidence that Australia. ARPA-e and the Dutch project have all focused on this as one of their major research areas. However, given sufficient time and money, it is probable that this process can be made far more efficient than it currently is. Having said all of the above, there is

> nevertheless now a concerted push from many governments and the involvement of many research institutes and major technology companies, and it seems likely that the concept of ammonia as an energy carrier as part of a 'decarbonisation' strategy may be with us to stay.

Nitrogen+Syngas 350 | November-December 2017

THE CULTURE OF INNOVATION



AMMONIA NITRATES & PHOSPHATES UREA MELAMINE METHANOL SYNGAS

FULL ENGINEERING SERVICES



Southbank House, Black Prince Road London SE1 75J, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

BCInsight

CONTENTS

What's in issue 350

Power to ammonia

COVER FEATURE 1

COVER FEATURE 2

Prospects for

COVER FEATURE 3

Fertilizers from

COVER FEATURE 4

debottlenecking

NITROGEN+SYNGAS

NOVEMBER-DECEMBER 2017

Nitrate plant

gasification

Indian urea



PROCUREMENT AND PROJECT MANAGEMENT



CONTENTS

What's in issue 350

□ COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

NITROGEN+SYNGAS ISSUE 350 NOVEMBER-DECEMBER 2017

BCInsight

Southbank House, Black Prince Road London SE1 75J, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

The prospects for Indian urea

India has unveiled plans to end urea imports by 2022. However, many such pronouncements have come and gone over the years – is this one any more likely to come to fruition?

arlier this year, India's government announced ambitious plans to end imports of urea within five years. As India is currently the world's largest importer of urea, and has completed no new urea plants since 1999, this has raised eyebrows in international markets. Can the government achieve its dreams of returning to the kind of self-sufficiency in nitrogen production that India enjoyed in the 1990s?

Economy

10

18

23

28

As China's economy has slowed, it had been hoped by many around the world that India would be able to somehow compensate. For a while this looked to be the case - India's economy grew at a very high rate of 9.1% for 10 2016. Since then, however, growth has slowed quarter by quarter, to 7.9% in 2Q 2016, 7.5% in 30 2016. 7% in 40 2016 and 6.1% in 10 2017, and the most recent figures show a further slump to 5.7% for 20 2017. Some of the blame has been placed on the government decision to withdraw 1.000 and 500 rupee notes from circulation in an attempt to reduce the size of the off-books economy and encourage more payment of income tax - widely avoided in India's largely cash economy. The introduction of the Goods and Service Tax in July has likewise caused uncertainty in the run-up to its imposition. However, this has been very much a sectoral slump - services continue to expand at 8.6%, while manufacturing is down to a 1.2% expansion for 20 2017, compared to 10.7% a year previously, due to widespread de-stocking, and agriculture, which accounts for 15% of GDP. grew by 2.3%. A bigger structural problem

is unemployment and under-employment, as much investment has been in capitalintensive industries which do not employ many people. Nevertheless, current forecasts see India's economy recovering to 7-8% growth over the next few years.

Agricultural demand

 in While it now has shrunk to only 15% of GDP, agriculture continues to be a vital part of the Indian economy, employing more than 50% of the working population and supporting 58% of rural households.
Agricultural exports represent 10% of India's exports and the country ranks 3rd

Fig. 1: Fertilizer use, India, 2016-17

16.2%		DAP
15.1%		NPK
7.7%		SSP
5.2%		Potash
1.3%		Others
Source: The Ferti	liser	Association of India

> Nevertheless, India's food grain production rose by 8.7% in the 2016-17 financial year, to a record 273 million t/a, including a 4.5% increase in rice production and a staggering 37% increase in pulses, thanks in part to a good 2016 monsoon after a couple of poor years, and the government is targeting a similar figure for 2017-18 after a monsoon that delivered 95% of average rainfall from July-Seotember this year.

AMMONIA

MELAMINE

METHANOL

SYNGAS

URFA

NITRATES & PHOSPHATES

sidy (NBS) scheme steadily falling since its

in this worldwide. However, while India's

growth in agricultural productivity since independence has been a remarkable success story, in recent years productiv-

ity has fallen, and rice yields per hectare

are 47% lower than in China. Crop intensity and irrigated area continue to rise:

overall, IFA predicts that cereal production in India will rise by 7%, with the gain coming almost exclusively from enhanced

productivity. Development of irrigation and

better use of rainfall water will be influ-

ential. But in order to markedly increase

productivity, more and better balanced

fertilizer use is required. India's aver-

age application rate is around 150kg nutrients per hectare, 50% lower than for

neighbouring Bangladesh and barely one

incomes and the ability to buy fertilizer.

The government has attempted to main-

tain food security and enhance farm

incomes via minimum support prices

(MSPs) for major agricultural commodi-

ties, revised and up-rated each year to

ensure that there was a rising floor to agri-

cultural prices, helping to stabilise income

increases and guarantee farmers a return

The main hurdle to this lies in farm

third of China's rate.

Fertilizers

peak in 2011.

India's fertilizer market is dominated by urea. As Figure 1 shows, applications in the 2016-17 farm year (July-July) were 54.5% of all fertilizer use. Because of its importance to Indian farmers, India has always fallen outside the NBS scheme,

Nitrogen+Syngas 350 | November-December 2017

www.nitrogenandsyngas.com



What's in issue 350

CONTENTS

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

NITROGEN+SYNGAS ISSUF **NOVEMBER-DECEMBER 2017**



Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

Urea production

heavily than other fertilizers. This has had the unfortunate effect of over-emphasising India's urea consumption has historically its use at the expense of other nutrients run at around 30 million t/a, rising to such as phosphorus and potassium, lead-32 million t/a in the 2015-16 farm year ing to some of the stagnation in farm proalthough, as noted above, it fell for the ductivity, as well as continuing to make it first time in several years for the 2016too important to switch to a lower subsidy 17 growing season. Current projections system. It is currently not clear to what are for modest growth in nitrogen conextent this will change once India switches sumption, of the order of 1.5% per year. to the new subsidy system - so-called Set against this, domestic production has direct benefit transfer or DBT, in which the lagged some way behind, reaching about 22 million t/a in 2015-16, leading to 8 fertilizer subsidy is paid direct to farmers to encourage them to purchase it rather million tonnes of urea imports. The reason than to manufacturers. This has already for this has been an effective moratorium been trialled in some areas of the country, on building new urea plants since 2000. and is due to be rolled out nationwide on While India struggled through the 1990s to achieve self-sufficiency in urea production, In the meantime, cheap agricultural subsidies were high and feedstock availurea has also had the side-effect of it being ability was expensive or uncertain - many smuggled out of fertilizer markets and into plants used naphtha as a feedstock, which industrial uses, such as the manufacture of was increasingly expensive due to high oil plywood/particle board, the smoothing of prices, and even when the government textiles, and even as a common adulterant forced them to change to natural gas feed-

tackle this, as well as to eke out India's limmeant that allocations to fertilizer producited domestic supplies of urea, the Indian ers were also frequently cut. government has responded by mandating India's shortage of natural gas has that all urea sold in India must now be been a perennial issue for the fertilizer coated with neem oil, at a rate of 350ppm industry, which represents a large slice of per tonne. Neem is a tree in the mahogany India's natural gas consumption. Indian family native to India, and India has 60% of gas production actually peaked at 49 bcm the world's neem trees. It is fast growing in 2010, according to BP. Since then it has and happy with low water conditions. The fallen year on year, and in 2016 dropped government attributes this to the increase another 6% to 27 bcm. At the same time, in grain production last year in spite of an gas consumption has also fallen, mainly apparent 2 million t/a drop in urea condue to lack of availability, from 61 bcm to sumption for 2016-17 to around 28 million 45.7 bcm in 2015, although last year this t/a. As well as preventing diversion of urea increased to 50.1 bcm. This means that into other areas (estimated at 500.000 the country's gas deficit has increased. t/a), neem oil also slows down the rate from 12 bcm to 23 bcm, and this is made of hydrolysis of urea into ammonium and up with imports of LNG, 60% of which came then nitrate ions, which is the form in which from Qatar in 2016. India actually has conit becomes available to plants. In India's siderable untapped natural gas reserves, warm and moist climate, this can happy onshore in the northwest and northeast very rapidly, leading to the nitrogen leachof the country, and offshore in the southing to water or volatilising into the atmoseast and Bay of Bengal. In addition to this, phere before plants can absorb it. Slowing there are reserves of coalbed methane and shale gas which remain largely undedown the rate that this happens makes more nitrogen available to the plant and so veloped. However, one of the major issues increases the effect of each kilogramme of has been that government price controls on gas have made it uneconomical for companies to develop these reserves, and it is hoped that the slow liberalisation of

Finally, since June the government has also mandated that urea be sold in 45kg bags rather than 50kg bags, in the hope that this will lead farmers to less urea, arguing that a 45kg bag of neemcoated urea is equivalent to a 50kg bag of uncoated urea in terms of its nutrient try's ability to import gas by that time. This

India's gas industry may help with this. In the meantime, there are ambitious plans for new LNG import terminals, five of which are due to come on-stream in the period 2017-19, which should double the coun-

is important because - although gas represents only 7% of India's energy needs, with coal responsible for the vast bulk of them - India has huge coal production and reserves - one third of gas consumption is

by the fertilizer industry. If a shortage of natural gas is the main hurdle for expanding urea capacity, there remains the option of using coal gasification, which has been the preferred solution for China, and which could also be used by India, with its huge coal reserves. The development of coal-based urea capacity has however been coloured in India by its experience with two coal-based plants which were built at Ramagundam and Talcher in the 1970s, which suffered from all manner of production issues and which were finally closed down. In addition, the high ash content (35-45%) of Indian coal means that certain types of gasifier are not suitable. Nevertheless, there has belatedly been a push to develop more coal-based urea capacity, although this has not been stock, demands from the power industry without its own problems.

New urea policy

All of which brings us to India's current situation. There are 30 urea plants in India, many of them of considerable vintage, all of them converted to run on natural gas and many of them dependent on relatively expensive LNG as feedstock. Successive debottlenecking and improvements at these plants have led to a slow rise in capacity, and efficiency improvements to bring down gas consumption, but production of urea has also been hindered by gas availability and government efforts to keep a lid on subsidy payments by setting a cap on production from individual units called 'reassessed capacity' beyond which subsidy payment was linked to the so-called 'import parity price'.

In April 2017, the Indian government unveiled a \$8.5 billion plan to turn the country into a net exporter of urea by 2022. In addition to the moves already noted - coating of urea with neem and supply in smaller bags in an attempt to reduce consumption - production will be boosted by lifting the production cap and the rehabilitation of several older, mothballed plants as well as construction of new, greenfield capacity. The policy aims to help shield farmers against global price fluctuations and limit government subsidies, as well as tying in with Prime Minister Narendra Modi's 'Make in India' nush to boost domestic manufacturing, attempting to create more jobs.





AMMONIA NITRATES & PHOSPHATES UREA MELAMINE METHANOL SYNGAS

EP/EPC PROJECT **EXECUTION**

CASALE

casale.ch

www.nitrogenandsyngas.com

Nitrogen+Syngas 350 | November-December 2017

January 1st 2018.

urea spread on the field.

effectiveness.

13

14

18

23

25

28

30

and the government subsidises it more

in milk because it is so chean. In order to

What's in issue 350

Power to ammonia

COVER FEATURE 1

COVER FEATURE 2

Prospects for

COVER FEATURE 3

Fertilizers from

COVER FEATURE 4

debottlenecking

NITROGEN+SYNGAS

NOVEMBER-DECEMBER 2017

BCInsight

Southbank House, Black Prince Road

Nitrate plant

gasification

Indian urea

CONTENTS

New capacity

INDIA

10

13

16

18

20

22

23

25

28

29

30

Current plans call for the re-start of five idled urea plants previously operated by the Fertilizer Corporation of India (FCI) and Hindustan Fertilizer Co. Ltd (HFCL). The plants are at Barauni in Bihar state. Sindri in Jharkhand, Talcher in Odisha, Ramagundam in Telangana and Gorakhpur in Uttar Pradesh. Major state utility companies such as Gas Association of India Itd (GAIL) and Coal India Ltd (CIL) are involved in financing and providing feedstock for the units, which will be operated by existing fertilizer firms. CIL and the National Thermal Power Corporation (NTPC) have formed a joint venture to revive the FCI plants in Sindri (in conjunction with the Indian Oil Co.) and Gorakhpur, with feedstock to be sourced from GAIL's proposed new Jagdishpur-Haldia pipeline, which will bring LNG from the northeast coast at Haldia into the inte-

rior of Littar Pradesh This would also connect to the former HFCL Barauni unit.

At Talcher, the aim is to effectively scrap the old facility, which closed in 2002, and build a new 1.2 million t/a ammonia-urea plant based on coal gasification as a feedstock with investment cost put at \$1.2

billion. This includes opening up a new coal mine 8km from the plant site itself and moving 500 families who currently live on the land to be occupied by the mine. A new operating consortium has been formed from FCI, Gas India Ltd (GAIL), Rashtriva Chemical and Fertilizer Ltd and Coal India Ltd. Gorakhpur, Sindri, Talcher and Barauni together would add a total capacity of 7.5 million t/a of urea, in theory making India approximately self-sufficient. Commercial production at the four new plants is targeted for 2021/22.

However, in addition to these rebuilds at brownfield sites, there are also greenfield developments around the country. Foremost is Matix Fertilizers in West Bengal, where construction is complete and the plant is in commissioning. The aim is to run the 1.3 million t/a facility from coalbed methane sourced in the local area. from the Essar Oils Jharia and Raniganj coal fields 30 km away. A pipeline has been constructed and Essar says that it has now achieved sufficient production to feed the plant.

FCI site at Ramagundam in South India (originally one of the two coal gasification plants), where Ramagundam Fertilizers, a joint venture between FCI, National Fertilizers Ltd and Engineers India, is spending \$810 million to build a new 1.3 million t/a gas-based ammonia-urea plant. The targeted start-up date is currently 2019. Chambal Fertilizers and Chemicals, which shut down its old plant at Kota near Gadepan in Raiasthan state in 2015 due to unfavourable economics, is now building a new 1.3 million t/a plant at the site, with completion also set for 2019.

The government has also approved the establishment of a new brownfield ammonia/urea complex at the Brahmaputra Valley Fertilizer Corp (BVFCL) site at Namrup in Assam, where a new 860,000 t/a ammonia-urea plant will replace the two older 220,000 t/a and 270,000 t/a units, while the fertilizer ministry

Affordability is one thing, though, and availability is another...

Power to build a coal gasification plant in Angul, Odisha, and by Adani Group to develop a coal to power and urea facility with a substitute natural gas (SNG) side stream. If all of these plants were to end up being built, India would be a major net exporter of urea

A note of caution

One thing that India has never been short of is urea project proposals; over the past 20 years, governments have considered and discarded dozens of them, and a degree of cynicism regarding the current batch may well be justified. Securing financing and securing feedstock at a competitive price have always been the major hurdles. While the government has definitely become far more enthusiastic about its backing ahead for new capacity, this has not necessarily translated into practical measures. For example, the Indian fertilizer industry suffers from a major backlog of unpaid subsi-

dies, which rose from \$2 billion in 2011-12

to \$8 billion in 2015-16. The involvement

of major Indian energy companies in the

Another project is the revival of the new project proposals may make financing easier, but does not ensure that all will be plain sailing when seeking money from major financial institutions.

> In terms of feedstock, the price of natural gas currently depends on a mechanism which weights domestic gas prices against a basket of international indicators, including the US Henry Hub, the UK NBP, the Alberta Reference Price and the Russian domestic gas price. This has led to a domestic gas price as low as \$2.60/MMBtu (recently increased to \$3.15/MMBtu), which is below ONGC's average cost of producing gas of \$3.50/ MMBtu. Furthermore, imported LNG which would be used to feed most of the new plants - is not price regulated, and so to overcome this the government

introduced its Gas Pooling Policy, which averages domestic prices with imported LNG to arrive at a final price to urea producers. This, and the current relatively low costs for LNG and lower gas prices is also studying proposals in the international hubs which set Indian to revive the loss-making domestic prices, mean that gas is cur-Madras Fertilizers Ltd and rently relatively affordable.

Fertilisers & Chemicals Affordability is one thing, though, and Travancore plants. There availability is another - in theory the Indian have been proposals by fertilizer industry at capacity requires 46.5 ONGC and CFCL to build million scf/d of natural gas, of which it a gas-based urea plant in receives a notional allocation of 31 mil-Tripura, by Jindal Steel and lion scf/d of gas, but in practice the actual delivered volumes have been only 22-24 million scf/d. The new pipeline and LNG import terminal projects may mean that there is more LNG available for urea producers, but this also exposes India to the peaks and troughs of the LNG market currently oversupplied, but no surplus lasts for ever.

The prospect of coal gasification on

the face of it seems a better one, but a move to coal increases capital costs and complexity. The Jindal project at Odisha and the RCF Talcher plant have both struggled along for several years and deadlines have come and gone with no earth having been turned at the sites. Talcher is looking to close financing next year via a bond issue and currently seems the more likely to make it, but there is still a long road

Still, the most likely consequence seems to be that 3 or 4 of these plants will be up and running by 2021-22, and India's net import of urea will be cut by 4-5 million t/a or so. It may not be selfsufficiency, but it is certainly a major step in that direction



AMMONIA NITRATES & PHOSPHATES UREA MELAMINE METHANOL SYNGAS

INDIVIDUAL **CUSTOMER** CARE



London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

Nitrogen+Syngas 350 | November-December 2017



■ CONTENTS What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

NITROGEN+SYNGAS ISSUE 350 NOVEMBER-DECEMBER 2017



Southbank House, Black Prince Road London SE1 75J, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com





29

30

Inspired by *The School of Athens*, Raffaello Sanzio 1509-1511 Vatican Museums. Photo Scala Archives Ammonia Nitrates & phosphates Urea Melamine Methanol Syngas

A FULL RANGE OF TECHNOLOGIES AND SERVICES



What's in issue 350

Power to ammonia

COVER FEATURE 1

COVER FEATURE 2

Prospects for

COVER FEATURE 3

Fertilizers from

COVER FEATURE 4

debottlenecking

NITROGEN+SYNGAS

NOVEMBER-DECEMBER 2017

BCInsight

Nitrate plant

gasification

Indian urea

CONTENTS

RUSSIA

Last year JSC Ammonium, a leading Rus-

sian producer of mineral fertilizers, offi-

cially commissioned a new plant for the

production of ammonia in the city of Men-

deleevsk in Tatarstan, one of Russia's

most economically developed regions. The capacity of the plant is 700.000 t/a

of ammonia per year and 717,500 t/a

of granulated urea, while the volume of

20

21

22

23

25

28

29

30

Major investments in Russia's nitrogen production



Eugene Gerden reports on the continuing growth in Russian nitrogen fertilizer production, as SDS-Azot begins work on a new line for production of ammonium nitrate at Kemerovo.

he production of nitrogen fertilizers in Russia will significantly increase in the coming years, due to the recently begun expansion of one of country's largest facilities in the Kemerovo region. This is being carried out by the local SDS-Azot enterprise, SDS the Russian initials for the Siberian Business Union – has a diversified holding across various industries, including one of the largest coal mining companies in Russia (SDS Coal). It is also one of the largest producers of nitrogen fertilizer in Russia, with assets in Western and Eastern Siberia, including Kemerovo Azot, the Angarsk Nitrogen Fertilizer Plant and AZOT-Service. It is a primary supplier of ammonia nitrate explosives for mining customers in Siberia and the far east of Russia, as well as Mongolia and Kazakhstan.

The new plants are being built at the site of the existing SDS-Azot facility for the

production of nitrogen fertilizers and will result in a 50% increase in overall capacity at the site. Current production capacities at SDS-Azot are estimated to be 1.0 million t/a of ammonia. 1.0 million t/a of ammonium nitrate, 500,000 t/a of urea, 314.000 t/a of ammonium sulphate, and 116,000 t/a of caprolactam.

Expansion

The new project involves the construction of an ammonia plant with a capacity of 2,000 t/a, a 1,200 t/d nitric acid plant, an ammonium nitrate solutions plant with a capacity of 1,250 t/d, as well as a porous ammonium nitrate facility with a capacity of 1.000 t/d. Tecnimont, part of the Maire Tecnimont Group, has been appointed the lead contractor on the project, which is

expected to be the largest project in the Russian nitrogen fertilizer industry in the past 25 years, both in terms of production capacities and investments. Those investment figures for the project stand at 1.2 billion; the majority of funds are expected to be allocated from SDS-Azot's own resources, with the remaining being provided by Russian banks.

During the second stage of the project SDS-Azot plans to invest in the building of another line for the production of urea with a daily output of 2,200 t/d, as well as a new facility for the production of ammonium nitrate sulphate. In the longer-term, SDS-Azot intends to establish a production facility for sodium cyanide at the capacities of the same plant.

Roman Trotsenko, a well-known Russian businessman and a major shareholder of SDS-Azot, said that building the new facility will allow SDS-Azot to increase its current capacities by more than 1.5 times and become one of the largest nitrogen fertilizers' producers not only in Russia, but also in Europe. The company is already one of the largest chemical enterprises in the Urals and Siberia and, together with fellow SDS subsidiary Angarskiv ATK LLC, the company controls 85% supplies of ammonium nitrate to mining enterprises in Russia's Siberia and Far East regions. In addition, both companies produce together almost 30% of the total production of caprolactam in Russia, and control up to 50% of its exports from Russia.

Roman Trotsenko said building of the plant should be completed during the next 2-3 years. "The main goal is not only to increase output of the company, but also to switch to the manufacture of new products. which will be in high demand among both domestic and foreign customers of the company", Trotsenko said. He also added the company puts big hopes on the expansion of its Kemerovo plant, the volume of investments in which has already amounted to 9 billion roubles (US\$150 million) since 2010.

Growth in nitrogen

Analysts at the Russian Ministry of Industry and Trade said the project may be attractive to its investors, as nitrogen fertilizers are perhaps the only segment of the Russian fertilizer industry, which have demonstrated good growth rates over the past few years, even during the financial crisis in Russia during the period of 2014-2016, as well as this year. A spokesman for Denis Manturov, Russia's Minister of Industry and Trade, said that this was because the majority of revenues of leading local producers are calculated in the US dollars, while devaluation of the Russian national currency in international markets has provided additional support to them on the domestic market. At present the Russian nitrogen fertilizer industry continues to be mostly export-oriented. This, in turn, ensures a regular influx of currency to producers. At the same time large reserves of natural gas in Russia priced in roubles allow local fertilizer producers to undercut foreign markets

In recent years the production of nitrogen fertilizers in Russia has significantly increased and continues to grow, mainly due to stable demand from the domestic agricultural industry and large exports abroad. Analysts at the Russian Ministry of Agriculture predict that the demand for nitrogen fertilizers in Russia will continue to grow over the coming years, mainly due by the growth of consumption by local agriculture business, which is currently booming due to the continuing ban against food and agriculture exports from Western countries to Russia. In the case of agriculture, a spokesman of the Russian Minister of Agriculture Alexander Tkachev said that over the past few years local government has significantly increased the volume of its funding, and that a significant part of this has been allocated to the subsidies to domestic farmers for the purchases of fertilizers, including nitrogen. This has contributed to the growth of consumption of nitrogen fertilizers by the Russian farming industry in recent years.

However, where Russia produces about 20 million t/a of fertilizers however domestic consumption accounts for only around 15% of total production, equivalent to 2.6 million t/a, and in spite of the ongoing growth of domestic consumption and exports. Russian analysts fear that further commissioning of new capacity may lead to excessive supply of

some types of mineral fertilizers to the domestic market, Igor Kaluzhsky, Executive Director of the Russian Association of Mineral Fertilizer Producers (RAPU), has predicted that over the next few years the volume of production of nitrogen fertilizers in Russia will be by almost 10 times higher than the country's annual needs in these fertilizers

While SDS Azot will be a major contribinvestment in its building amounted to utor to this growth in fertilizer production. US\$1.6 billion. The company plans to it is not the only project which involves build another line for the production of the establishment of a large-scale plant ammonia with the same capacity during for the production of nitrogen fertilizers. the next several years.



In today's competitive syngas markets, the costs associated with unplanned downtime are high.

Quest Integrity Group's Reformer Care solution is an integrity management system for the entire steam reformer. Our proprietary inspection technologies capture 100% of the data for the internal and external tube surfaces. Combined with our advanced engineering analysis and assessments, Quest Integrity enables you to minimize the risk of unplanned downtime and make confident real-time operating decisions.

- · Failure mechanisms identified and guantified Fitness-for-service and remaining life assessments in
- accordance to API 579/ASME FFS-1
- Temperature correction software for more accurate tube temperature measurement

Ensure your steam reformer is operating at full capacity for longer.



www.nitrogenandsvngas.com

Nitrogen+Syngas 350 | November-December 2017

Nitrogen+Syngas 350 | November-December 2017

www.nitrogenandsvngas.com

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577

Web: www.bcinsight.com www.bcinsightsearch.com

15

18

19

23

25

28

29

30

Ammonia market developments

A look at some of the factors shaping merchant ammonia supply. demand and patterns of trade worldwide.

n 2016, global ammonia capacity stood at around 218 million t/a, of which around 175 million tonnes of ammonia was actually produced that vear. Most ammonia produced is for captive use, particularly in downstream urea. ammonium nitrate, nitric acid or ammonium phosphate plants, and the merchant market remains a small fraction of this - 18.3 million tonnes in 2016, or around 10% of total production.

On a regional basis, as shown in Table 1, it can be seen that the major net importing regions continue to be North America (mainly to feed DAP production in Florida. Western Europe (for a variety of uses, often industrial/technical). South Asia (mostly to feed Indian DAP and some urea production) and East Asia (Japan, South Korea, Thailand and Taiwan are all net importers, again often for industrial/technical uses). By nation, the largest importers are the United States (26% of all imports), India (15%), and then Morocco, Korea, Belgium, Germany, Taiwan and France,

On the export side, the major volumes come from Trinidad, which was responsible for 25% of ammonia trade in 2016, Russia (20%) and then in decreasing order Saudi Arabia, Algeria, Canada, Indonesia, Qatar, Iran, the Netherlands and Australia, which collectively represent another 40%. One notable omission from that list is Ukraine. which exported only 180,000 tonnes of ammonia in 2016, and so dropped out of the top 10 ammonia exporters. The largest exporting regions were thus South and Central America (chiefly because of Trinidad's contribution), the former Soviet Union (because of Russia) and the Middle East (because of the Saudi, Qatar and Iranian volumes)

While demand for ammonia ultimately comes mainly from fertilizer applications

Table 1: World ammonia production. consumption and trade. 2016. million t/a product

Region	Production	Export	Import	Consumption	Net imports
Western Europe	11.2	. 1.1	4.0		2.9
Eastern Europe	5.2	0.2	0.2	5.2	0
FSU	22.6	3.9	0.5	19.2	-3.4
North America	17.4	1.4	4.8	20.8	3.4
S/Central America	9.0	5.0	1.2	5.2	-3.8
Africa	7.4	1.5	1.5	7.4	0
Middle East	16.5	3.3	0.7	13.9	-2.6
South Asia	18.9	0	2.7	21.6	2.7
East Asia	65.2	1.5	2.8	66.5	1.3
Oceania	1.7	0.4	0	1.3	-0.4
Total	175.1	18.3	18.3	175.1	
Source: IFA					

(about 75% of all ammonia produced), this nitrogen is mostly traded internationally as the more readily portable urea or ammonium nitrates, and so it is the rarer, nonintegrated fertilizer or industrial users who represent the buying side of the market, particularly diammonium phosphate producers, as they tends to gravitate towards sources of phosphate rock, which often do not coincide with sources of gas or coal to make ammonia. Conversely, merchant ammonia production is generally from large, relatively inaccessible sources of natural gas close to

Recent developments

The figures show some major changes over the past couple of years. There is higher production in the US, South Asia Africa (mainly Algeria but also Egypt) and the Middle East (Iran and Saudi Arabia), and lower production in East Asia (due to

waterways where export can be facilitated.

Chinese production curtailments) and the FSU. The fall in FSU production is mainly accounted for by developments in Ukraine. which exported 1.3 million tonnes of ammonia in 2013, but less than 300,000 tonnes in 2016, as the ongoing struggle against separatists in the east and gas curtailments and price increase from Russia continue to affect the industry there. Consumption has increased in the

FSU, North America and especially Africa (mainly Morocco, as OCP continues to expand diammonium phosphate production) the Middle East (Saudi Arabia - also for DAP production) and South Asia. There has been falling consumption in Eastern Europe and East Asia.

New capacity

Ammonia capacity additions have increased sharply in the past two years and are projected to peak this year, before falling back towards 2019. Most of this capacity is integrated into downstream production, but often ammonia-urea plants are designed to operate with a slight excess of ammonia capacity, providing an additional income stream and incremental exports. In the next couple of years, major standalone ammonia capacity additions will come from EuroChem at Kingisepp in Russia in 2018 (1.0 million t/a) as well as some additional merchant ammonia from Acron at Novgorod and PhosAgro at Cherepovets.

Elsewhere, Indonesia is adding another 660.000 t/a of merchant ammonia capacity, and Saudi Arabia will have around 500,000 t/a spare from the Wa'ad Al Shamal phosphate complex. Mexico has plans to re-start two idled ammonia plants at its Cosoleacaque facility, which would reduce the country's import requirements. Although India has some new ammonia-urea units under development, as our article elsewhere this issue indicates, there would be no free ammonia from these, as they are all geared towards reducing urea imports.

However, the largest tranche of new capacity has come from the continuing development of domestic US ammonia capacity, most of it based on cheap natural gas - the product of the continuing boom in shale gas production. During the 1990s the US ammonia industry in effect decamped to Trinidad, as domestic gas prices rose in the US, to the extent that Trinidad had been exporting two thirds of US ammonia requirements. But as plants have re-started and new capacity has started to come on-stream, so US imports of ammonia have fallen. US ammonia imports fell from 6.8 million tonnes in 2010 to 3.4 million t/a in 2016, and are

> 0. Watch Integer's market outlook

completed Some 2.0 million t/a of new ammonia capacity was added in 2016 at CF industries in Donaldsonville - all of it integrated into downstream urea and UAN production - and at Dyno Nobel's Waggaman plant, eliminating imports to feed AN production. Another 2.5 million t/a is due to be commissioned in 2017-18, including CF's Port Neal plant, Iowa Fertilizers at Wever, Simplot at Rock Spring and the BASF-Yara plant at Freeport most of these are also integrated plants. but the BASF unit will be a 750,000 t/a standalone unit

set to fall still further as new capacity is

China's changing fertilizer market

China continues to be the other major influence on nitrogen markets. While China has been a major exporter of urea. on the ammonia side exports have been small or even negative, because the producing locations, tied to major coal fields, are often some way inland. In 2016. China imported a net nearly 500,000 tonnes of ammonia, making it the 9th largest importer. Some of this was because of continuing rationalisation of Chinese ammonia and urea capacity and government environmental audits which have sought to reduce pollution near urban areas and which have forced seasonal closure of a considerable tranche of capacity. At the same time, China is attempting to move to a 'zero growth' fertilizer consumption policy by 2020, although increases continue to occur in industrial uses such as acrylonitrile and caprolactam, and scrubbing of sulphur dioxide emissions

from coal-fired power plants.



AMMONIA

On the demand side, Morocco is curr-

ently engaged in a major expansion of its

domestic phosphate production capacity

and is looking towards much greater pro-

duction of downstream phosphate fertiliz-

ers, mainly MAP and DAP. Out to 2021.

OCP is adding a planned 6 million t/a

of phosphate capacity (tonnes P_2O_5).

which will require a corresponding

increase in ammonia imports of about

Morocco seems set to provide a boost

to what has been a fairly depressed mar-

ket. Although the Wa'ad Al Shamal DAP

plant in Saudi Arabia has eaten into that

country's surplus, the new capacity in

the United States will continue to dis-

place merchant ammonia into other mar-

kets. This year should see the peak of

new capacity additions, especially in the

United States, and there are indications

that the current seasonal low in prices

may be the low point for the ammonia

industry. However, demand growth for

nitrogen fertilizers, accounting for 75%

of ammonia demand, has slowed in

recent years, and in future may only rise

at around 0.7-1.2% per year, depending

on China's success in capping fertilizer use. Fastest growth is now most likelv in

Factors to watch will be gas price avail-

ability in Trinidad, still the world's larg-

est ammonia exporter, and the ability of

producers in Ukraine and other Black Sea

producers to act as swing capacity.

South America

Morocco

1 9-2 4 million t/a

A low point for prices?

CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

NITROGEN+SYNGAS **NOVEMBER-DECEMBER 2017**

BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

A report on papers presented at the 62nd Safety in Ammonia Plants and Related Facilities Symposium, held in September in Brooklyn, New York.

Safety in ammonia plants

he American Society of Chemical Engineers (AIChE) has been running its Safety in Ammonia Plants and Related Facilities Symposium - otherwise known as the Ammonia Safety Symposium - for over 60 years now, and it continues to be the pre-eminent forum for discussing ammonia plant incidents and trying to improve process operations. Perhaps it is a sign of the success of the Symposium that a number of papers described safestart-ups and commissioning of plants or methods of achieving reliability. However, there is of course no place for complacency when dealing with large and complex chemical facilities.

15

18

19

20

21

22

23

25

28

29

30

The human element is often the root cause of process safety accidents, and so the Symposium's keynote speaker. Tony Downes of Honeywell, looked at 'abnormal situation management'. He identified 70% of process incidents as being humanrelated, either directly (40%) or indirectly by operating equipment out of its normal operating range (30%). Critical to making the right decisions, he said, was the display hierarchy on the operator's terminal.

allowing them to move from 'big picture' to detail as the situation warrants. It is also important not to overload operators with unnecessary process alarms, and to simplify complex information by making it more visual. Tools like an alarm configuration manager can reduce the number of daily alarms by a factor of 100 and in a real world case led to one fewer plant 'trip' per year, saving hundreds of thousands of dollars.

Ammonia plant incidents

There were fewer incidents described this year, but the Fertilizer Association of India had put together the results of its most recent five-yearly surveys of safety at Indian fertilizer plants, and presented this to the Symposium. This survey, covering 2010-2015, showed an encouraging fall in the Long Term Injury Rate (LTIR) to 0.36 per million man-hours worked, compared to 0.59 for the previous survey period (2005-2010), although this average figure masked a considerable range from 0.04 for the best performing to 0.89 for the

worst. There was also a 50% reduction in the 'severity rate' (man-hours working time lost per million man-hours) from the previous survey period, as well as an increase in reportable injury-free operating days. There were nevertheless still 29 fatalities during the reporting period, half of them resulting from a slip/fall from height. Road/rail vehicle accidents and electricity-related incidents covered another seven. Other causes included fire, steam scalding, and entanglement with moving equipment.

Fatima Fertilizers in Pakistan had likewise performed a study on all papers from the most recent 20 years of previous Ammonia Safety Symposia in order to try and extract key learnings for their own plants' operation. Their study shortlisted papers to identify common themes and underlying trends which would have relevance to their own site. It found that 52% of reported incidents were due to operating failure, 26% design failure, 18% mechanical or metallurgical failure, and 4% down to instrument failure. Operational failures were more common in the 'front end' of ammonia plants, design and metallurgical



CONFERENCE REPORT

CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

Neither.

www.nitrogenandsvngas.com

Count on an extremely fast, easy installation with Blasch's patentpending StaBlox* Tunnel System customizable interlocking blocks and highly engineered, mortar free expansion joints.



BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

Nitrogen+Syngas 350 | November-December 2017

failures more common in the 'back end'

of the plant. Fatima also highlighted the

key lessons taken from the most relevant

rence of more dangerous incidents.

Chambal Fertilizers and Chemicals Ltd had a leak of boiler feed water into the

shell side of the steam generators, leading to contamination of the process gas

and steam carry-over into the low tem-

perature shift section. The plant was shut

down to preserve the LTS catalyst, and so

that remedial action could be taken with

the waste heat boiler. A slow drving of the

catalyst had to be performed to prevent

issues with a syngas compressor, which

when opened was found to be partially

blocked with ammonium carbamate depos-

its. Fault tracing identified the interac-

tion of leaks in the feed-effluent gas heat

exchanger downstream of the methanator

and the presence of ammonia in the sour

gas recycle to the compressor as the cause

of this previously unreported phenomenon,

and their paper also described work with

simulators and the corrective actions taken

On the technology side, Haldor Topsoe

launched their new SvnCOR Ammonia

technology for large-scale plants. This

takes a leaf from their previous SynCOR

Methanol and GTL technologies, the for-

mer of which was launched in 2014 and

is now under construction at a 5,300 t/d

methanol plant, while two 7,000 t/d (in

terms of ammonia equivalent) GTL units

are expected to be completed in 2019.

to ensure that it did not recur.

Technology

Fauji Fertilizers suffered efficiency

breakage.

process improvements.

papers and how they had related it back to are removed prior to the ammonia synthesis loop, with pure nitrogen provided from In other operating incidents, Yara Pilthe air separation unit, allowing a single bara reported on a high pressure syngas ammonia converter. Topsoe says that this compressor failure in 2015 due to reverse flowsheet can deliver a 6,000 t/d single rotation. It appears that two synloop valves stream ammonia plant. There will be a full did not fully close during a trip (caused by article on this new technology in our next a site electrical blackout due to a seawaissue, January-February 2018. ter piping rupture) allowing the synloop to On the materials side, the Special Metals Corp. showcased the performance of rapidly depressurise, and a check valve remained open. The revere rotation allowed their Inconel alloy 693 in resisting 'metal the resonant frequency to be passed five times in succession, leading to the failure. Baker Engineering and Risk jointly presented with Koch Fertilizer on how minor failures can be precursors to larger equipment failures, and the case for more thoroughly reviewing and investigating such failures as a way of preventing the occur-

Briefly, it replaces the steam reformer with dusting' or attack by high activity carbon. an oxygen-blown autothermal reformer and typically from high concentrations of carfired pre-heater. Carbon dioxide and inerts bon monoxide in syngas. This can lead to rapid pitting and eventual disintegration of metal components into a metal and carbon powder, exposing fresh material to attack. Inconel 693 is a nickel-chrome allov with iron and aluminium and trace quantities of titanium and niobium. The combination of chromium and aluminium seems to be the key resistance factor, and the alloy exhibits 10,000 times the metal dusting resistance of, e.g. Inconel 600, which has only

0.2% Al instead of 3% Al.



15

18

22

23

25

28

29

30

Fertilizer production via the gasification route

India has abundant sources of coal which can be utilised as a raw material for producing fertilizers. N. Mangukia of Linde Engineering India discusses the benefits of large scale ammonia/urea plants based on the gasification of coal or petcoke for countries like India. which is currently a large importer of fertilizers.

orld food demand is increasing in conjunction with the increase in world population. Some countries like India are still large importers of fertilizers. The feedstock for producing fertilizers (i.e. natural gas) is either not available in some countries or it is not economically viable to produce fertilizers from costly imported feedstock (e.g. RLNG). An alternative feedstock for producing fertilizers is coal or petroleum coke (petcoke) if available. India has abundant sources of coal which can be utilised as a raw material for producing fertilizers.

The most vital raw material for producing fertilizers is ammonia which can be produced by the following routes: reforming of natural gas or naphtha;

 partial oxidation of fuel oil or LSHS; coal or petcoke gasification.

In the case of India, due to limited avail ability of natural gas feedstock, high prices and ultimately marginal or no viability, there have been no major Indian fertilizer projects in recent years. The dependence on imported fertilizer continues and is directly linked to food security. Indigenous gas production from the Krishna Godavari (KG) basin has not followed original projections and hence is not encouraging for fertilizer producers. All of these factors point to sourcing of feedstock from alternative sources such as coal or petcoke

Alternative promising feedstocks

Coal and petcoke are promising alternative feedstocks for fertilizer production due to large reserves in many countries and their cost competitiveness with other

feedstocks like natural gas/ naphtha/ LSHS. Various gasification technologies have developed in recent years which helped to utilise coal/petcoke for production of not only fertilizers but also other valuable products. Some countries like China have used the gasification route to such an extent that the major share of ammonia production is produced via the gasification route. Although gasification has the highest specific energy consumption for ammonia production of all routes available, due to the relatively very low cost (in \$/million Btu) for coal/petcoke. the production costs are lower.

Production scheme

Fig. 1 shows a simplified production for the production of nitrogen fertilizer via the gasification route.

Air separation unit (ASU)

Cryogenic ASUs separate atmospheric air into pure oxygen, which is used for gasification, and pure nitrogen, which is used for ammonia synthesis. Mega capacity ASUs are built around the world with very high reliability. A standard 2,200 t/d ammonia plant requires an ASU with a capacity to produce 3,500 t/d

oxygen. The main components of an ASU comprise a large main air compressor (MAC) and booster air compressor (BAC). air dryer station, cold box for cryogenic separation of air, expansion turbine for generation of required cold energy, liquid oxygen pump, and nitrogen compressor. Liquid storage for oxygen and nitrogen can be considered depending on project specific requirements.

Gasification

Depending on the type of feedstock (i.e. coal with varving ash content, petcoke etc.), gasification technology needs to be selected. The gasifier converts the feedstock into syngas (a mixture of mainly carbon monoxide, hydrogen and small amounts of carbon dioxide and methane). Gasification reactions take place at medium to high pressure in the presence of oxygen and steam. After heat recovery, the syngas is routed to the shift reaction section to convert carbon monoxide and water into hydrogen and carbon dioxide by the water gas shift reaction in the presence of catalyst

Acid gas removal (AGR)

There are two types of acid gas removal (AGR) process: physical wash or chemical





wash. The Rectisol® process is an exam-Nitrogen wash unit (NWU)

ple of a physical wash process. It offers an excellent solution for gas treatment downstream of the gasification complex. Treated gas can be utilised for cogeneration (as fuel to existing gas turbines), fuel for existing heaters, producing value added products like hydrogen, substitute natural gas (SNG), carbon monoxide (CO), synthesis gas, etc.

Rectisol® was developed jointly by Linde and Lurgi in the late 1950s and both companies own the IP rights. The Rectisol® process uses methanol as the wash solvent. The process operates best at low temperatures and high pressures. The process can be used for the selective removal of H_oS. COS and CO₂. The handling of trace impurities like hydrogen cyanide, ammonia, metal carbonvls, chlorides etc, is essential,

Fig. 2 shows a simplified acid gas removal scheme using Rectisol.

Acid gas removal plays an important role in a gasification complex as it is located between the gasification unit and the final product processing units. The AGR removes all the undesirable components from the synthesis gas and provides valuable side streams such as an enriched H₂S fraction for the production of elemental sulphur, and pure CO₂, etc. Carbon dioxide, which is available from the AGR, is required for urea production.



The liquid nitrogen wash unit is an economical and highly reliable step for ammonia syngas purification and preparation. The NWU

- takes high pressure nitrogen from the ASU. The two principle functions of the NWU are: removal of impurities such as CO, Ar
- and CH₄ from syngas; addition of required stoichiometric amount of nitrogen to the hydrogen stream to

achieve the correct H2:N2 ratio of 3:1 Carbon monoxide will poison the ammonia synthesis catalyst, while argon and methane are inerts that will build up in the loop and slow the reaction

- The main advantages of the nitrogen wash unit are:
- high purity of ammonia syngas leading to long catalyst life in converter:
- no accumulation of inert gases in ammonia synthesis loop; no purge required hence losses of syn-
- gas is eliminated: • simple operation – no moving parts like
- pumps and compressor.

Ammonia synthesis

Once syngas with the required stoichiometric proportion is available from the NWU, a state of the art ammonia synthesis unit can be employed for production of ammonia. Various configurations of ammonia converter are available from experienced licensors. The ammonia synthesis section of a plant utilising gasification as the route

for synthesis gas preparation is no different to an ammonia plant with natural gas or nanhtha as feedstock

Challenges

The main challenges for producing fertiliz-3. Haberle T and Geraghty C. (Linde Engineer ers via the gasification route are: the coal available in certain countries

has a high ash content which poses a

CONTENTS

GASIFICATION

challenge as regards the handling of

route due to a relatively high capital cost

cost competitiveness of the gasification

· reliability yet to be proven in some

Large ammonia/urea plant capacity is

• All individual process units such as the

• Although the energy consumption per

ASU, AGR, NWU, and ammonia synthe-

sis are available for capacities of more

tonne of ammonia would be higher, due

to lower energy cost of coal/net coke

the production cost of ammonia will be

lower than conventional feedstocks like

duced through this route (e.g. methanol,

· Various other products can also be pro-

New gasification technologies have

· Issues of high ash content can be miti-

• Environmental issues need to be

1. Coal gasification as a route for viable Urea-

2. Mangukia N.: "Acid gas removal by Rectisol®

Wash Process", Chemical industry Digest

ing): "Keys to optimized & integrated proj-

ects" presentation at GTC_San Francisco

Ammonia plant (by RCF Mumbai)

emerged in recent years which eliminates

problems related to reliability/availability

gated by blending high ash coal with

low ash coal and using petcoke from

addressed by using suitable methods

for handling ash (lowering fly ash).

possible via the gasification route.

than 2,500 t/d ammonia.

natural gas/naphtha.

• Sulphur is a by product.

SNG etc.)

of gasifiers.

refineries

References

(June 2013).

(Oct 2011)

large quantities of ash;

countries.

Summarv

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

NITROGEN+SYNGAS **NOVEMBER-DECEMBER 2017**

BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577

Web: www.bcinsight.com www.bcinsightsearch.com

www.nitrogenandsvngas.com

A China first at Henan Jinkai ammonia plant

M. Rizzi of Casale and Xu Junhong of Henan Jinkai Group provide a short history of Casale ammonia synthesis technology for inert-free loops and its application in the design of the largest single-train inert-free ammonia synthesis loop built and operating to date: the 2,000 t/d Henan Jinkai ammonia plant in Kaifeng, China.

he operating conditions in an ammonia synthesis converter are more severe when the synthesis gas is generated by gasification than when it is generated by the more common steam reforming process. The gasification route has to be used in plants fed with heavy feedstocks such as coal

13

18

19

20

21

22

24

25

26

27

28

29

30

The reason for the high operating severity is that the synthesis gas entering the synthesis loop has much lower concentrations (in the order of hundreds of ppm) of inert components (principally argon and methane) than are found in synthesis gas from steam reforming plants. Consequently the gas is more reactive, which means that operating temperatures can be significantly higher.

The parts of the synthesis section that are most critically influenced by the higher severity are the ammonia converter itself and downstream equipment items like the steam superheater, the waste heat boiler and the boiler feed water preheater. The effect on the remaining parts (standard heat exchangers, vessels, pipes, etc.) is no more critical than usual for the design and operation of the plant.

Casale ammonia converters

One of Casale's principal activities is developing new and original designs for ammonia synthesis converters and related equipment items. Over the last 30 years Casale designs have been used in about 200 new or revamped ammonia converters, i.e. almost half of all ammonia converters in operation worldwide were designed by Casale.

Recent history of Casale's inert-free converters and synthesis loop includes

the revamping of existing converters as well as many new synthesis loops in new plants, most of them supplied in China. the world's most important fertilizer manufacturer using coal as feedstock. China has committed to making massive investments in the fertilizer field with the aim of becoming self-sufficient in fertilizers and. at the same time, shutting down the oldest, least efficient and sometimes polluting existing small plants.

The scope of Casale's responsibility for the synthesis loop has commonly included not only the supply of the converter internals and engineering, but also the supply of the heat recovery device (boiler, BFW preheater or steam superheater) downstream of the ammonia converter.

In these plants it is evident that it is not only the converter design that is of critical importance but also the hottest heat recoverv device located just downstream of the converter outlet nozzle.

In such a position, where process conditions are very challenging (high temperature, very high ammonia concentration, hydrogen partial pressure still very high), the construction details of the converter and the heat recovery device make all the difference between long and trouble-free operation and problematic and sometimes

discontinuous operation Casale's axial-radial converter experience with an inert-free loop dates back to the end of the 1980s, when Casale revamped an existing two-bed quenchcooled converter in a 1970s ammonia plant, in Germany. Casale chose a threebed configuration with two quenches at the inlets of the second and third beds. This converter has been in operation since July

1989. At the beginning of the new century Casale supplied a fourth bed for this plant which increased its capacity to 2,200 t/d. at the same time achieving energy savings. The second installation of an inerts free loop was in Araucaria, Brazil, where the existing cartridge was replaced with a new, three-bed, two interchanger Casale design. The third installation was for a new ammonia plant of 1,000 t/d for Farmland, in Coffeyville, Kansas, USA. This plant has been in operation since September 2000.

Many more installations have been implemented in subsequent years and today there are more than 40 inert-free converters/synthesis loops in the world designed by Casale (about 30 of them on stream) and another 15 are under construction or ready for start-up, most of them in China. These plants have capacities ranging from 150 to 2.000 t/d. Casale has recently acquired other

contracts in China for three new synthesis loops with capacities of 1,250, 1.800 and 1,820 t/d.

Peculiarities of inert-free synthesis loops

The inert-free synthesis loop is a feature of ammonia plants in which the synthesis gas is generated by gasification of a heavy feedstock, usually coal. Because of the way in which the synthesis gas is purified. components of the synthesis gas that are inert in the synthesis loop (noble gases. particularly argon, from the atmosphere and methane) are removed to very low levels, typically a few hundred ppm in total. That is low enough for it to be unnecessary to purge inerts from the synthesis loop, as methane and argon are sufficiently soluble in the HP liquid ammonia product for

balance between the rate of introduction in the make-up gas and the rate of removal in the product to be reached at a much lower concentration in the circulating gas than is normal in the synthesis loop of a steam reforming ammonia plant with loop

purge. Casale consider a synthesis loop to be 'inert-free' when the inert molar concentration $(CH_4 + Ar)$ at the converter inlet (recycle + make-up gas) is lower than about 2 vol-%.

The design of the hottest parts of the synthesis loop is more critical for a loop using inert-free syngas than for a traditional loop in a steam reforming plant. Nonetheless, inert-free loops do have some advantages over traditional purged loops, particularly from an energy point of view

In the absence of a continuous purge. almost the entire amount of hydrogen produced in the front end section is ultimately converted to ammonia. Because of the higher reactivity of the mixture fed to the converter, the required production can be achieved at a lower operating pressure than would be needed in the equivalent traditional synthesis loop with inerts

For the same reason (higher partial pressure of the reactants), the circulation flow at a given production rate is lower. making it possible to use smaller size equipment and also reducing the energy consumption in the loop itself.

All in all, the result is a higher synloop energy efficiency and lower capex for a given rate of production. Their relative influence on the overall operating economics is affected by site specific factors, and the best compromise is therefore determined through a case by case analysis in which the two main parameters are energy cost and equipment cost.

In any case, since the cost of a synthesis loop can account for up to 20-25% of the total investment cost in a new coalbased ammonia plant (and up to 30% in a gas-based steam reforming plant), the economic advantage of capex reduction is significant.

It should be noted, however, that the higher reactivity of the synthesis gas entering the converter has a potential drawback. Because of the closer equilibrium approach in the ammonia synthesis reaction, on average the temperatures at each bed outlet are higher than normal for a traditional converter. This is especially true for the first bed, where the partial pressures of the reactants are at their maximum and

the driving force for ammonia synthesis is consequently at its strongest.

The severe conditions at the converter bed outlets have to be properly managed to cal features and materials of construction prevent untimely failures or problems with that can reliably withstand the challenging the internals. In addition it is essential to environment at the outlet of each bed. have a uniform temperature distribution of Where appropriate, these advances have the gas at each bed inlet, that means very been implemented in the hottest parts of little temperature discrepancies. This is due all Casale converters, increasing the relito the much faster reaction rate when comability of internals generally. pared to converters fed with syngas containing inerts, and makes reaching the optimum temperature profile inside the converter more critical. The reason lies in a steeper profile of reaction rate vs temperature. This steeper profile means that the on/off transition of the synthesis reaction across the threshold temperature happens in a few degrees Celsius rather than in about ten degrees as in the inerts containing loops. Therein lies Casale's success in inertfree synthesis loops. In the first place, in the Casale converter incoming cold gas is

passed through the gap between the cartridge and the inside wall of the pressure vessel to protect it from potential damage by abnormally high temperatures and the aggressive chemical composition.

Secondly, Casale has incorporated independent temperature control at each bed inlet, which prevents overheating at the bed outlets.

In addition, the mixing device installed in Casale converters, designed with the help of a computational fluid dynamic (CFD) program, guarantees very good mixing, despite the low pressure drop required: that makes it possible to enter the beds with a practically uniform temperature profile, making possible temperature

Fig. 1: Henan Jinkai ammonia synloop (Plants I and II)

Henan Jinkai plant Henan Jinkai fertilizer complex in Kaifeng

converter shutdown

with its three single train ammonia plants of 2,000 t/d each is the biggest fertilizer installation in China All three plants have been designed by Casale at different times. The first two twin

plants started up just a few months apart during 2013 (the first reached full capacity in March and the second in September). and the third plant is under construction.

Technical aspects

The make-up gas comes from a coal gasification unit and the pressure at compressor suction is 30 bar g.

AMMONIA SYNTHESIS LOOP

optimisation without the risk of unwanted

Casale has also developed mechani-

The design operating pressure of the synthesis loop (Fig. 1) is 139 bar g and the total inerts content at the converter inlet (methane plus argon) is 1.32 mol%.

The converter configuration is a three bed two interchanger design, a typical high efficiency solution chosen for Casale new converters, since it maximises ammonia conversion per pass.

The heat recovery train consists of a high pressure BFW preheater, working at 140 har g



www.nitrogenandsvngas.com



CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

NITROGEN+SYNGAS **NOVEMBER-DECEMBER 2017**

BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

Nitrogen+Syngas 350 | November-December 2017

www.nitrogenandsvngas.com

To contain investment cost, a single start-up heater common to the two lines. has been installed

The third plant, not yet in operation, has a different configuration in the heat recovery train downstream of the ammonia converter. Instead of the HI-IP BFW preheater used in trains one and two, the third train has a MPS BFW preheater, the relevant MPS boiler and the MPS superheater (placed at the converter exit nozzle). Another difference in the two designs is the single syngas compressor in the third train compared with double twin compressors in the first two trains. In addition, the third plant has a dedicated start-up heater. The refrigeration section is quite stand-

ard (Fig. 2). It is equipped with two chillers and its only peculiarity is that for the Rectisol unit and air separation unit (ASU) a dedicated refrigeration section has been designed (not in the Casale scope of supply). The same design will also be used in the third plant.

Project history

12

13

15

18

20

21

22

23

24

25

28

The contract for the first 2.000 t/d ammonia plant in China, in Jinkai, was signed at the end of November 2009. The Casale scope of supply consisted

of the following:

- converter internals (Casale proprietary)
- BEP of the high pressure section (from
- compressor suction to
- the synthesis loop) and the refrigeration section
- Check of detail engineering
- Site services (installation, supervision, commissioning and start-up supervison, plant optimisation, operator training).

Casale's engineering department faced a challenging schedule for a plant with a capacity never designed before, especially for the size of machinery and equipment involved (for example to satisfy Jinkai Chemical's request to buy the two twin syngas compressors from the domestic market.

The engineering of the first ammonia train in Jinkai started in early 2010 (EDC 7 January 2010)

The BEP first issue was dispatched at the end of April 2010

As per all Chinese projects Casale worked in collaboration with local design institutes, typically playing the role of EPC contractor of the project. For the two proiects mentioned, the design institute was Beijing Aerospace Wan Yuan Coal Chemical Engineering Technology Co. It was involved

www.nitrogenandsvngas.com

Table 1: Main operating data: test run vs design data

	Design conditions (SOR)	27-28 March 2013 test run
Time on stream, months	0	~4
Plant load, t/d	2,000	2,032
MUG consumption, Nm ³ /h/t of ammonia	2,694	2,650
Operating pressure at converter outlet, bar g	139.0	129.0
Inerts at converter inlet, mol-%	≤ 1.30	0.96
NH ₃ at converter outlet, mol-% (simulated value)	20.1	19.9
Source: Casale		





in the project since the very preliminary phases, so that the design basis was agreed during contract negotiation. BEP was provided by Casale in both

English and Chinese language and according to relevant Sinopec standards. After BEP or PDP delivery, a design

review meeting was held with the participation of the client and design institute experts, in which Casale gave detailed explanations and the client reviewed and commented on all of the basic design documents, allowing the design institute to proceed with the detailed engineering work. Henan Jinkai Group and design institute participants in this meeting comprised a delegation of about ten people including

project managers and experts from all the major engineering disciplines, such as process, mechanical, piping, instrumentation,

Detail engineering design was then developed by a design institute and Casale reviewed this work to check compliance with the process design requirements. The project ended with a detail design review meeting in the offices of the design

The collaboration between Casale and the client continued in the field. The installation of converter internals and the first catalyst loading was performed by the client under the supervision of field engineers.

Casale assistance continued with commissioning and start-up activities, including catalyst reduction. During this period Casale personnel also provided training to client staff operators. Final commitments for site activities were concerned with opti-

mising parameters and the test run. Due to the strong co-operation between all parties involved, the plant was completed and commissioned in only one and a half years after the effective start of engi-

neering activities. Catalyst loading in the first train was completed in October 2012, the catalyst reduction was completed at the end of November 2012 and the plant reached nominal production in March 2013, mainly due to some

delays in trimming the front end section. The successful test run certificate was signed at the end of March 2013. Full capacity and all other guarantees have been achieved with an operating pressure 10 bar lower than design.

Fig. 3: 3-Bed-2-intechanger

Source: Casale

have reached 20.6%.

first one

converter

2,100 t/d) without any problem.

ing pressure had been raised to the design

value, the ammonia concentration would

Later the plant reached 105% load (i.e.

The second twin train was designed

The contract for the third 2.000 t/d

and erected practically in parallel with the

train was signed on October 2014 and

Casale scope of supply was also extended

to the MPS superheater downstream of the

expected to be ready for start-up in 2017.

This plant is under construction and is

Nitrogen+Syngas 350 | November-December 2017



sis converters is a three bed, two interchanger design with axial-radial flow in the catalyst beds (Fig. 3).

converter design are:

- three bed, two interchanger design:
- and well proven design of internals;
- conditions deriving from independent control of temperature at each bed inlet; easy optimisation linked to a very smooth
- avoiding unexpected loss of reaction; reliability due to the mechanical design Table 1 shows the main operating data for the test run compared to the design of the internals and choice of material
 - easy catalyst replacement (loading and unloading) thanks to the full opening of upper cover and modular construction

Most of the points listed are already well known. What is worth highlighting with regard to point 4, is that the mixing devices installed in the converter, to provide uniform temperature at the bed inlets. are the result of detailed simulations developed with the help of CFD. The design requires the knowhow to achieve near perfect mixing between two stream with big differences in both flow and temperature, while maintaining a very low pressure drop



The typical Casale design for new synthe-The main advantages of the Casale

Fig. 4: Direct connection with BFW preheater

high conversion per pass thanks to the

- easy and stable to run due to simple
- flexibility of operation under transient
- data. It should be noted that if the operatof construction:
 - of internals.

sure drop of the converter is not affected. Thanks to these characteristics, Casale converters are highly reliable and efficient. They are able to withstand literally hundreds of start-ups and shutdowns; very high internal temperatures, for example, because of the absence of inert gases in gasification based plants; and decades of operation. Several Casale converters have been running for more than 20 years without any maintenance.

Casale also has strong experience in the design of the critical downstream equipment for process heat recovery, i.e. the steam superheaters and waste boilers. temperature profile at the bed inlet. which are installed in many of its synthesis loops in gasification plants. To further improve this part of the plant, Casale has developed a direct connection between the converter outlet nozzle and the downstream exchanger, which completely eliminates the connecting pipe (Fig. 4), resulting in a less costly arrangement that is also more reliable as a pipe at this point is subject to high temperature, nitriding, hydrogen attack and mechanical stress. To withstand such severe conditions would require special and expensive materials, while in the Casale design all of these problems are eliminated. Casale has supplied a considerable

number of these special direct-coupled exchangers (superheaters, boilers and BFW preheaters) for inert-free loops; about 20 boilers, six steam superheaters and two HP BFW preheaters.



CONTENTS

What's in issue 350

Power to ammonia

COVER FEATURE 1

COVER FEATURE 2

Prospects for

COVER FEATURE 3

Fertilizers from

COVER FEATURE 4

debottlenecking

Nitrate plant

gasification

Indian urea

BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

electrical etc

institute

Nitrogen+Syngas 350 | November-December 2017

10

12

13

18

19

20

21

22

23

25

28

29

30

Driving methanol plant efficiency

The gas heated reformer is an alternative to the steam methane reformer in syngas plants, providing a more cost effective, compact and energy efficient unit that minimises environmental impact. M. Janardhanan of Johnson Matthey outlines where the technology has come from and where it is heading to, highlighting the benefits of its use in applications, particularly in Iran where water consumption is very important.

vnthesis gas from natural gas has for a long time been generated within a steam methane reformer (SMR) sometimes used in conjunction with an autothermal reformer (ATR). Gas heated reforming (GHR) has promised to revolutionise the generation of synthesis gas for ammonia, methanol and hydrogen for over 25 years by way of replacing the large and expensive reformer with a more cost effective, compact and energy efficient unit that minimises environmental impact. Recent changes, especially in the energy sector, have prompted many to relook at the benefits of gas heated reforming where electrical power is increasingly being generated by renewable energy. Similarly, where water resource is scarce, the use of a gas heated reformer can cut the raw water use by half when compared to an SMR+ATR flowsheet.

Johnson Matthey has continued to build on the work of Imperial Chemical Industries (ICI) to develop gas heated reforming technology, and is able to demonstrate that gas heated reforming is the preferred technology for synthesis gas generation for multiple applications.

Technology selection for synthesis gas generation has a significant effect on CO₂ emissions and raw water consumption in a methanol plant. The scope of this article is to look at the impact of technology choices on raw water consumption in a methanol plant based on natural gas feedstock.

The effect of CO2 emissions on technology selection has been discussed in a paper by A. Ingham¹. The following assumptions have been made for the comparison: Methanol plant is stand alone with no.

www.nitrogenandsyngas.com

power import.

 Power is generated inside battery limit tubes. Catalyst in the reformer tubes will (ISBL) with a steam turbine except drive the gas to equilibrium for the water for the advanced combined reforming gas shift reaction (2) and close to equilib-(ACR) flowsheet where a gas turbine is used

- limit (OSBL) for flowsheet with CO₂ addition • The turbine condenser is cooled with
- cooling water. Where the air cooler is placed upstream

of a cooling water exchanger, the intermediate process temperature is set to synthesis

Synthesis gas generation from natural gas

60°C (140°F).

A range of technologies are available for the production of synthesis gas in methanol plants. These can be broadly classified as below with each, other than advanced combined reforming, having the option to include a pre-reformer:

- conventional SMR: conventional SMR with CO₂ addition (SMR+CO₂):
- combined reforming (CR), SMR followed by ATR:
- ACR, GHR followed by ATR.

Steam methane reforming is the process of converting hydrocarbons into an appropriate synthesis gas containing carbon oxides and hydrogen. The overall reaction is strongly endothermic and requires considerable amounts of heat input. Fuel is burned to generate hot combustion gases that surrender their heat to the reacting gases through the walls of the reformer

rium for the steam methane reaction (1). • CO₂ is imported from outside battery Steam methane reaction $CH_4 + H_2 O \rightleftharpoons CO + 3 H_2$

Water gas shift reaction

 $CO + H_2O \rightleftharpoons CO_2 + H_2$ Overall chemical equation for methanol

 $CH_4 + H_2O \rightleftharpoons CH_3OH + H_2$ (3)

(1)

(2)



SMR with CO₂ addition

- $3 \text{ CH}_4 + 2 \text{ H}_2\text{O} + \text{CO}_2 \rightleftharpoons 4 \text{ CO} + 8 \text{ H}_2$ (4) Overall chemical equation for methanol synthesis
- $3 \text{ CH}_4 + 2 \text{ H}_2\text{O} + \text{CO}_2 \rightleftharpoons 4 \text{ CH}_2\text{OH}$ (5)

Autothermal reforming is a process whereby oxygen is mixed with a steam/ natural gas mixture in a fuel rich combustion zone. This generates high temperatures and is followed by an adiabatic catalyst bed, driving the reaction to equilibrium in both the steam methane and water gas shift reactions, combined in equation (6).

Nitrogen+Syngas 350 | November-December 2017

ATR

 $2 \operatorname{CH}_4 + \operatorname{O}_2 \rightleftharpoons 2 \operatorname{CO} + 4 \operatorname{H}_2$ (6) Overall chemical equation for methanol synthesis

$2 \text{ CH}_4 + \text{O}_2 \rightleftharpoons 2 \text{ CH}_3 \text{OH}$ (7)

In a flowsheet with only ATR technology to generate synthesis gas, a mixture of natural gas and steam mixture is pre-heated in a fired heater. The feed gas temperature to the autothermal reformer has to be limited due to the risk of carbon formation by hydrocarbon cracking in the pre-heater tubes. To overcome the undesirable process feed conditions, the process uses excess oxygen to raise the outlet temperature to the target value of 1,020°C (1,870°F) and consequently, the synthesis gas that an autothermal reformer produces is short of hydrogen. Typically, the overall equation (8) for an ATR based process is:

Overall chemical equation for methanol synthesis

 $CH_4 + 0.65 O_2 \rightleftharpoons$ $0.9 CH_2OH + 0.2 H_2O + 0.1 CO_2$ (8)

To improve the carbon efficiency and achieve the stoichiometric synthesis gas, hydrogen is required. This can be achieved with a steam methane reformer or gas heated reformer installed upstream of the autothermal reformer

A combined reforming flowsheet avoids the limitation of the autothermal reformer feed inlet temperature by replacing the fired feed gas pre-heater with a steam methane reformer. In an advanced combined reforming flowsheet a heat-exchange reactor, the GHR, is installed upstream of the autothermal reformer. Heat is recovered from the autothermal reformer effluent stream both as sensible heat and reaction heat into the endothermic steam methane reaction. The combination of a steam methane reformer and an autothermal reformer or a gas heated reformer and an autothermal reformer in series (shown in Fig. 1) yields a synthesis gas that is stoichiometrically balanced for methanol production for a range of natural gas feedstock compositions.

Typically, the overall equation (9) for a combined reforming/advanced combined reforming based process is:

Overall chemical equation for methanol synthesis

 $CH_4 + 0.49 O_2 + 0.02 H_2 O \rightleftharpoons$ $CH_{3}OH + 0.02 H_{2}$



Fig. 1: Advanced combined reforming flowsheet

Raw water consumption

Synthesis gas production from natural gas is a water intensive process (see Fig. 2). The primary consumers of water in a methanol plant are:

- demin water plant make-up;
- cooling tower make-up

Demin water plant make-up

Most demin water consumption is by direct water addition to process and steam system make-up. Theoretical process water requirement is 0.57 tonne of water per



tonne of methanol for the steam methane reforming only flowsheet and 0.35 tonne of water per tonne of methanol for the steam methane reforming with CO₂ addition flowsheet. With a typical 95% methanol synthesis loop carbon efficiency, the process water consumption is 0.62 and 0.37 tonne per tonne of methanol respectively for steam methane reforming and steam methane reforming with CO2 addition flowsheets (Fig. 3).

The process water make-up require ment for both the combined reforming and advanced combined reforming flowsheets



Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

CONTENTS

What's in issue 350

Power to ammonia

COVER FEATURE 1

COVER FEATURE 2

Prospects for

COVER FEATURE 3

Fertilizers from

COVER FEATURE 4

debottlenecking

NITROGEN+SYNGAS

NOVEMBER-DECEMBER 2017

Nitrate plant

gasification

Indian urea

(9) Nitrogen+Syngas 350 | November-December 2017

www.nitrogenandsvngas.com

15

18

20

21

22

23

24

25

27

28

29



is 0.04 tonne per tonne of methanol. Steam system losses are approximately 0.08 tonne per tonne of methanol for all the flowsheet arrangements.

Cooling tower make-up

Cooling tower make-up is a major consumer of raw water in a methanol plant, Cooling water consumption for different flowsheet arrangements are compared in Fig. 4.

Superheated high pressure steam (HPS) is generated during synthesis gas production in methanol plants with steam methane reforming and/or autothermal reforming. The generated HPS is used for the compression of synthesis gas and /or air separation unit (ASU) turbo-machinery based on the technology selection.

In steam methane reforming, steam methane reforming with CO₂ addition and combined reforming flowsheets, more than 50% of cooling water is consumed by the turbine condensers. The advanced combined reforming flowsheet with gas heated reforming technology is unique when compared with all other flowsheets; no super-

	SMR	SMR+CO ₂	CR	ACR
Net feed and fuel (LHV basis), GJ/tonne MEOH	32.32	30.98	29.70	29.29
Net raw water makeup, tonne/tonne MEOH	2.28	1.78	2.39	1.20
CO ₂ emissions, kg/tonne MeOH	428	356	286	264
Source: Johnson Matthey				

www.nitrogenandsyngas.com

the capital cost of the project and does ig. 5: Gas efficiency LHV basis (GJ/t of methanol)

23.98

drive the compressors in the ASU and the

bined reforming plant by others:

ing the cooling water demand.

Where oxygen is available, either by pipe-

line or from an ASU operated by others, the

option to import power to drive the com-

pressors is a good choice. This reduces

and readily available.

the ISBL plant.

process

26.94 25.5

not impact the overall process efficiency. This option is not possible with a combined reforming process based on a steam methane reformer as the steam produced by the process is required to drive the ASU

turbines, otherwise it would be wasted.

STAMI UREA

Gas efficiency

In steam methane reforming, steam methane reforming with CO2 addition and combined reforming flowsheets, fuel is burned to supply heat for the endothermic steam methane reaction. The waste heat from the reformer is generally recovered by raising high pressure steam.

The fact that heat from the autothermal reformer effluent is being recycled directly back into the process though the gas heated reformer means that there is no direct combustion of any natural gas fuel to provide heat for the endothermic steam methane reaction.

heated high pressure steam is produced in Fig. 5 compares the gas efficiency of the different technology flowsheets and This gives the opportunity to select the Table 1 compares performance between optimum approach for providing power to the flowsheets.

synthesis gas compression required in the Conclusion

- Three options are available in addition The gas heated reformer recycles the high to supplying oxygen to the advanced comtemperature process heat and decouples HPS generation and methanol: no longer a Gas turbine power generation with dispower plant making synthesis gas.
- The ACR flowsheet offers the followtribution to electric motor drives, which eliminates the need for steam turbine ing advantages relating to energy and raw driven compressors in the plant, reducwater use:
- · Maximised waste heat recovery and liq- Power import from the grid. This is the uid effluent recycle to the process resultlowest capital cost option and is a good ing in the lowest energy consumption.
 - alternative if power is reliable, cheap Lowest raw water consumption. · Where sea water is used for cooling,
- · Gas turbine drive plus heat recovery, less heat rejection reduces the capex which is the lowest energy solution. on a sea cooling system having expensive titanium alloys.
 - Flexibility to import power and have the lowest carbon footprint.

References

1. Ingham A.: "Low carb methanol – the lighter way to produce methanol", IMTOF 2015.

Acknowledgement

This article is based on the paper "Driving methanol plant efficiency with a focus on the environment" by M. Janardhanan of Johnson Matthey and was produced as part of the IMTOF 2017 book.

Nitrogen+Syngas 350 | November-December 2017

LAUNCH A NEW UREA PLANT

BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

ADV.MNCE EVOLVE AN OLDER PLANT AN EXISTING PLANT Decrease Emissions NITROGEN+SYNGAS

Stamicarbon

CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

Nitrate plant debottlenecking and modernisation

Plant assets are the most valuable part of any chemical manufacturing business and should be looked after as carefully as possible. Casale has wide experience of many different types of plants thanks to its revamping activities. **J. F. Granger** of Casale discusses the latest trends for the modernisation of nitrate plants.

asale's revamping approach can be applied to nitrates plants, regardless of the original process design. It is therefore possible to modernise existing units to improve their efficiency and increase their capacity such that the revamped plant can compete with the most modern units in terms of reliability, safety and economics of production.

Modernisation of ammonium nitrate solution plants

Apart from the case where equipment is at the end of its life, the main targets for modernising ammonium nitrate plants is usually to increase the capacity, improve the quality of the process condensate and decrease the energy consumption required to achieve the desired concentration.

Capacity increase

18

At the heart of any ANS plant is the mixing of nitric acid and ammonia. Modifications made to increase capacity are usually very limited and focused mainly on the heat exchangers that preheat the raw materials and condense the additional process steam generated in the reaction. The nitric acid heat exchanger is not normally a problem as it is very small, the only consequence is to feed the acid at a lower temperature which will result in a less concentrated ANS. Apart from that, the ammonia vaporiser must

be able to achieve the duty to ensure that all of the ammonia is superheated

and vaporised to prevent emissions and

safety risks due to the production of

acidic ANS. Some minor modifications

to the reactor may also be required to

cope with the new load. In conventional

processes, the turbulence caused by the

reaction can result in strong vibrations of

the entire supporting structure which can

suffer severe damage. In the case of a

pipe reactor process, simply changing the

pipe reactor itself is sufficient to accom-

modate the new capacity.

To improve the quality of the process condensate may require greater modification. The easiest modification is to change the control parameter of the ratio control system from the pH of the ammonium nitrate solution to the pH of the process steam. If that is not enough, additional process steam treatment may be required. For example, the Casale purification exchanger was installed in a conventional plant in the early 2000s to generate a stream of very pure condensate containing less than 50

NITRIC ACID N1000 - MONOPRESSURE PROCESS N2000 - DUAL PRESSURE PROCESS

- Large capacity with single burner
- Highest efficiency
- Zero emissions
- Fully referenced
- Integrated Ammonia and NA production chain.

Southbank House, Black Prince Road London SE1 75J, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

BCInsight

www.nitrogenandsyngas.com

13

18

23

25

28

29

30

mg/l of AN. The system uses part of the process steam generated by the reaction to re-evaporate and purify the process condensate. Two steams are generated: • very pure condensate (as mentioned

above); concentrated condensate, which can be recycled to the nitric acid plant or used as make-up water for scrubbing granula-

tion plant exhaust gases. About two thirds of the process condensate can be generated in very pure form. A general scheme of the Casale system is shown in Fig. 1.

Emission treatment can always be improved in an existing plant by generating

Table 1: Material flows after installation of prill fattening at two French fertilizer plants

3rd 1998

	Fertilizer diameter (mm)	Prill feed (t/d)	Slurry to fattening (t/d)	Plant capacity (t/d)	Additional ANS (t/d)
Grandpuits plant					
Before	2.2	900		900	
After	3.3	300	600	900	(
Rouen plant					
Before	2.2	600	-	600	
After	3.3	600	1,200	1,800	1,200

a smaller quantity of contaminated water.

The Casale purification exchanger can be

installed in a conventional process or a

pipe reactor plant to limit the concentra-

tion of contaminants in the excess water

to less than 50 mg/l, which is the limit

for human consumption according to EU

Directive 98/83/EC adopted on November

limited revamp of the plant. In such cases

Reduced energy consumption

Source: Casale

Casale recommends the most efficient and economical way is to change the technology to the pipe reactor process.

Modernisation of granulation processes

Modernisation of the granulation process is usually aimed at debottlenecking the plant or improving the quality or range of products without changing the main equipment such as the granulator and dryer in a conventional granulation loop or the prilling tower in a prilling process.

Fattening

When producing ammonium nitrate fertilizers by a prilling process, both of these objectives can be achieved by just adding a fattening system (Fig. 2). In this system, prills are fed from the bottom of the prilling tower and are enlarged with some additional slurry provided from the same source as the prilling tower or from an alternative source. It is thus possible to produce granules up to 1.5 times bigger than the prills, while multiplying the capacity by a factor of 3. In the meantime, the nitrogen content of the fertilizer can be adjusted down to 25% N by adding some filler to the slurry fed to the fattening system.

Two examples of this system were installed in France in the early 1990s. The French market for fertilizer was demanding bigger granules and the fattening system was installed to enlarge the size of the prills from about 2.2 mm to 3 3-3 4 mm

In one plant at Grandpuits the total capacity of the plant was kept constant. In If it is not possible to decrease the energy the other plant at Rouen, the capacity was consumption to achieve a defined concentrebled. In that case, the additional ANS is produced by a new plant based on Casale tration with an existing conventional process, it is generally not possible with a pipe reactor technology. The results are shown in Table 1

Dual pipe reactor

For granulation plants producing NPKs, Casale recommends the dual pipe reactor technology for both increasing the capacity and enlarging the range of products which can be produced. In comparison with the pre-neutraliser process, the same granulation loop can deliver more than 30% more product without major modifications to the main equipment (granulator, dryer, crushers, screens, etc.). An added benefit is a reduction in the specific fuel consumption: introducing a pipe reactor in the dryer, the heat of reaction of a part of the phosphoric acid becomes available for drying the product (Table 2).

Modernisation of UAN processes

Casale is in the unique position of having in-house technologies and experts for all the different processes for producing UAN from natural gas and is therefore able to optimise any type of UAN plant to get the best out of them

The UAN process itself is quite simple, and in fact most of the work needed to improve its production lies in the upstream

Table 2: Specific fuel consumption for DAP production

40	12
50	8.8
60	4
	40 50 60

plants (urea, nitric acid and AN solution extent that liquid emissions are reduced plants) and in improving the integration even when the urea solution has been probetween them duced at a low concentration Points which have to be considered are:

- All of these processes use ammonia as a raw material but, depending on the recovery system employed, sometimes gaseous ammonia is available from the urea plant which can be reused and fed
- to the other plants. • The nitric acid plant generates HP steam as a byproduct which may be usable in the urea plant

 If the AN solution plant has proper process condensate treatment, it can generate clean condensate to be sent for disposal. That improves the water balance to the

COURT

energy savings in the urea plant. How to save time & money

As an example, a conventional neutraliser

producing 85% AN solution requires a urea

solution at a concentration higher than 75%

to produce 32% N UAN. The same 60%

nitric acid fed to a pipe reactor AN solution

plant will deliver ANS at a concentration of

92% minimum. Then the concentration of

the urea solution required for the same 32%

N UAN is below 70%. That means that the

urea plant can be debottlenecked without

modifying the concentration step; in addi-

tion, it also means that there will be some

Even the best equipment is subject to wear and tear. and that means expensive plant turnarounds. As a leading high-pressure vessel manufacturer in the nitrogen sector, we can save you time and money by performing the maintenance and in situ repair of your heat exchangers and reactors in the shortest possible time. And we can provide replacements, seeing to everything from design to installation.

We have all the know-how to work with all the materials involved - and a strong international track record of successful reference projects. Our highly skilled task force have already completed a large number of in situ works abroad.

So why not ask our specialists to advise you on your next in situ project?

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577

Web: www.bcinsight.com www.bcinsightsearch.com

www.nitrogenandsvngas.com

NITROGEN+SYNGAS

NOVEMBER-DECEMBER 2017

BCInsight

CONTENTS

What's in issue 350

Power to ammonia

COVER FEATURE 1

COVER FEATURE 2

Prospects for

COVER FEATURE 3

Fertilizers from

COVER FEATURE 4

debottlenecking

Nitrate plant

gasification

Indian urea

Table 1: Product specifications

Nitrogen content

Sulphur content

Moisture

Hardness

Bulk density

Source: tkIS

Diameter 2-4 mm

fertilizers is considered.

~ 21 wt-%

~ 24 wt-%

< 0.5 wt-%

~ 3.000 g

~ 90%

tendency during storage. Long term stor-

age tests are ongoing and results will

determine the transportation, storage and

coating requirements. The size of the gran-

ules is adjusted by screens in the process

to be compatible with other fertilizers. This

offers the opportunity for farmers to dis-

tribute the granules homogeneously and is also useful if bulk blending with other

The chemical composition is 21 wt-%

nitrogen and 24 wt-% sulphur (see Table 1).

Classification as fertilizer is defined by the

quality of the ammonium sulphate solution

used as feedstock. The process itself (Fig.

centrepiece of the production plant (see

Fig. 4). It is where the liquid ammonium

The fluidised bed granulator is the

3) does not jeopardise the classification.

750-850 kg/m³

CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com

www.bcinsightsearch.com

Fion cost by-product to premium AS granu

thyssenkrupp Industrial Solutions (tkIS) has developed a new fluidised bed granulation process to convert low cost by-product ammonium sulphate solutions into premium grade granules. Jens Mathiak of tkIS, describes the process and reports on the current status of the technology.

High-quality fertilizer for optimum plant growth

13

14

15

17

18

21

23

25

27

29

lant growth depends on the nutrient content of the soil. A balanced distribution of primary and secondary nutrients as well as microorganisms ensures an optimum crop yield. Nitrogen is an essential nutrient, and so is sulphur.

In today's world a cleaner environ ment tail gas desulphurisation and less acid rain now mean that soils especially those that are neutral or alkaline require the controlled addition of a fertilizer additive which contains sulphur: ammonium sulphate.

Ammonium sulphate feeds sulphur and nitrogen to the soil. With its colloidal components, the fertilizer binds to clay particles in the soil, ensuring a long-term supply of nutrients. Ammonium sulphate is thus perfect for plants with a long growth period and in areas with high rainfall. In addition to acting as a long-term plant nutrient, the sulphur also promotes the transfer of micronutrients, such as man-

ganese, iron and boron, from the soil to the plants. Ammonium sulphate solutions are a pertinent industrial by-product. In addition to sulphate, nitrogen and sulphur are key components of this fertilizer, which is mostly marketed in the form of crystals. In its state-of-the-art plants, thyssenkrupp has developed a process to convert

ammonium sulphate solution to granules.

The key advantages compared with liquid

and crystalline solutions are improved storage as well as spreading and mixing properties Alternative granulation plants are not

able to process ammonium sulphate solutions. These plants require expensive ammonia and sulphuric acid to achieve higher-priced premium product characteristics (see Fig. 1).

Low-cost granulation – premium prices

The granular form as a unique selling point and the high profit margin are two very good reasons to choose the thyssenkrupp ammonium sulphate process. In addition, due to the large quantities produced, crystalline ammonium sulphate is

Nitrogen+Syngas 350 | November-December 2017

a mass-market product while granulated ammonium sulphate is produced by only a few suppliers in relatively small quantities. Demand is accordingly high and there are also sales opportunities in niche markets.

The new process developed by thyssenkrupp offers the opportunity to convert low-cost by-product into valuable premium granules. The price for premium granules

Fig. 3: Fluidised bed granulation process for the production of ammonium sulphate

ig. 2: Ammonium sulphate

product prices

granules

compacted

Source: Integer Research

sulphate into granules

larger crystals

is significantly above the prices of stand-

ard products at around \$100 per tonne

Conversion of liquid ammonium

The fluidised bed granulation process

can produce ammonium sulphate with

a low moisture content to reduce caking

white crystals

other crystals

140

120

100

60

40

-20

(see Fig. 2).

Nitrogen+Syngas 350 | November-December 2017

Fig. 4: The fluidised bed granulator is the centrepiece of the production plant.

sulphate is turned into a solid product. The liquid ammonium sulphate solution is sprayed on the seed granules. The droplets stick to the small solid particle and the water phase is removed by applying hot air. Hence, the granules grow bigger in the fluidised bed granulator (see Fig. 5).

13

15

18

20

23

25

27

28

29

30

Downstream of the fluidised bed granulator the particles are screened in oversize. undersize and product granules. The oversize granules are crushed and returned to the inlet of the fluidised bed granulator together with the undersize particles. To maintain a stable process the particle balance has to be maintained. Therefor a partial stream of product granules can be recycled to the fluidised bed granulator as well.

The particles in the granulator are fluidised by a hot air stream. One option is to apply steam for air heating. If hot off

gases are available at the production site from adjacent plants these can be used to reduce operating costs. The air from the granulator is dedusted by scrubbing and sent to the environment as clean air.

can deviate quite significantly. On the Integration of this new process into other hand granulation can be a sensitive existing chemical complexes is essential process for some impurities. Hence, the for economic success. Besides the heat integration already mentioned there are pilot plant was not only used during the also opportunities within the combination development phase, but will also be utiof existing crystallisers. If a fluidised bed lised to test ammonium sulphate solutions granulation plant is installed parallel to a in the feasibility phase before deciding on crystalliser the load of the crystalliser will the investment of installing a fluidised bed be reduced. As a matter of fact this would granulation plant lead to the production of larger crystals. Reflecting the premium prices of larger crystals the economic benefit would be

References 1. Integer Research Limited "The global ammodouble: Higher prices for the granules pro-

nium sulphate market service". 2013. 2. Uhlemann, Hans: "Wirbelschicht-Sprühgranulation", Berlin, Springer, 2000.

produced in the existing crystallisation

Ammonium sulphate tends to produce dust and form granules with low hardness. The

toughest challenge during development

of the new process was to find a suitable

granulation additive. Mixing of the feed-

stock with the liquid additive is performed

before spraying the solution onto the seed

ating in batches. The core process param-

eters were identified and the granulation additive was selected. In a second phase

a technical scale facility was used to dem-

onstrate continuous operation and to identify extended process parameters like the recycle ratio. Finally upscaling was demon-

strated in a pilot plant which was built to

mitigate the risks and to demonstrate bal-

ance of plant. The pilot plant has a capac-

ammonium sulphate production uses

solutions as by-product from upstream

processes. The quality of these solutions

Approximately 85% of the global annual

The development started with a small lab scale single nozzles test facility oper-

Development of a new process

plant.

granules.

ity of 12 t/d.

duced in the new fluidised bed granulation

plant and higher refund for larger crystals

SAFETY IN AMMONIA PLANTS & RELATED FACILITIES SYMPOSIUM

THE CALL FOR ABSTRACTS **IS NOW OPEN**

63rd Annual Safety in Ammonia Plants and **Related Facilities Symposium** September 16 - 20, 2018 Sheraton Centre Toronto Hotel • Toronto, ON, Canada

Help ensure that the annual Ammonia Symposium remains a valuable resource for attendees by submitting your high-quality presentation. Submissions should feature the latest developments and best practices in the nitrogen and gas reforming industries with a focus on reliability and safety. Please submit your abstract proposal(s) to one or more of the following subject areas:

- ACCIDENTS
- SAFETY DEVELOPMENTS
- SAFETY STUDIES
- TECHNOLOGICAL ADVANCEMENTS
- MAINTENANCE IMPROVEMENTS

Download the Ammonia Conference Call for Abstracts Proposal Form at www.aiche.org/ammonia. Be sure to include a half-page summary of your abstract and email the form to Scott Rodrigue, Production Manager - CF Industries, at srodrigue@cfindustries. com. The deadline for abstract proposals is December 31, 2017.

If you have any questions about abstracts or would like to submit this proposal later than December 31, please contact Scott Rodrigue at srodrigue@cfindustries.com.

For general information about the Ammonia Symposium, please contact Ilia F. Killeen at 646-495-1316 or iliak@aiche.org.

The deadline for the abstract proposals is December 31, 2017.

SUBMIT YOUR ABSTRACT TODAY AT WWW.AICHE.ORG/AMMONIA

CONTENTS What's in issue 350 COVER FEATURE 1

SUBMIT YOUR

ABSTRACT BY

DECEMBER 31, 2017

e Global Home of Chemical Engineers

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567

Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

www.nitrogenandsyngas.com

Advertisers' index

Editor: RICHARD HANDS

LAURA CROSS

mike.nash@ihs.com Publishing Director: TINA FIRMAN tina firman@hcinsight.com

Subscription rates:

Subscription claims: Claims for non receipt of issues must be made within 3 months of

MARLENE VAZ Tel: +44 (0)20 7793 2569 Fax: +44 (0)20 7793 2577 marlene.vaz@bcinsight.com

TINA FIRMAN

KOICHI OGAWA

Takeuchi Building

1-34-12 Takadanobaba

Tel: +81 3 3208 7821

Fax: +81 3 3200 2889

Agents:

the issue publication date.

Advertising enquiries:

tina.firman@bcinsight.com

Tel: +44 (0)20 7793 2567

0.T.O. Research Corporation

Shiniuku-Ku, Tokvo 169, Japan

Previous articles from Nitrogen+Synga

and Nitrogen & Methanol from 1996

to the present are available digitally

in PDF format. To make a purchase,

Copyright: Issued six times per year,

or bi-monthly. All rights reserved.

reproduced, stored in a retrieval

or by any means - electronic.

mechanical, photocopying,

Copyright owner.

ISSN: 1750-6891 Design and production: JOHN CREEK, DANI HART

Printed in England by:

© 2017 – BCInsight Ltd

BCInsight

Published by: BCInsight Ltd Southbank House, Black Prince Road

London SE1 7S1 England

Tel: +44 (0)20 7793 2567

Fax: +44 (0)20 7793 2577

www.bcinsightsearch.com

Web: www.bcinsight.com

Buxton Press Ltd Palace Road, Buxton, Derbyshire

SK17 6AE

No part of this publication may be

system or transmitted in any form

recording or otherwise - without the prior written permission of the

or for a list of available articles, please see: www.bcinsight.com

Sales/Marketing/Subscriptions:

Cheques payable to BCInsight Ltd

Japan: (also subscription enquiries)

MIKE NASH

richard.hands@bcinsight.com Technical Editor: LISA CONNOCK

lisa.connock@bcinsight.com Contributors

laura.cross@integer-research.com

GBP 425: USD 850; EUR 655

Advertiser	Page	Website
AIChE Annual Safety in Ammonia Plants Symposium 2017	57	aiche.org/conferences
ANIVI Ingenieria SA	17	Anivi.com
Aumund	11	Aumund.de
Blasch Precision Ceramics	39	blaschceramics.com
Casale	23-31	casale.ch
Casale	32/33	casale.ch
Casale	51	casale.ch
Eurotecnica Contractors and Engineers	5	eurotecnica.it
Eurotecnica Contractors and Engineers	7	eurotecnica.it
Eurotecnica Contractors and Engineers	OBC	eurotecnica.it
Integer Research	IBC	integer-research.com
Johnson Matthey	IFC	matthey.com/
Nitrogen+Syngas Conference 2018	21	Crugroup.com
Schoeller-Bleckmann Nitec GmbH	53	christof-group.at/en/sbn/
Stamicarbon BV	49	Stamicarbon.com
Tecnimont Group	19	mairetecnimont.com/en

Distribution at: Nitrogen+Syngas 2018 Conference, **Gothenburg**, Sweden

Next issue: January/February 2018

- Utilisation of natural gas in large-scale complexes
- Packed absorbers for deep CO₂ removal
- New flowsheet for methanol production
- Gas market liberalisation
- New fertilizer capacity in the FSU
- Ammonium nitrate safety incidents

Closing date for advertisement space booking is 10 January 2018 For further information and to book advertisement space contact: Tina Firman, Publishing Director: tina.firman@bcinsight.com Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577

Over 6% year on year growth **forecast** for the value added fertilizer sector over the next decade.

Value Added Fertilizer Summit Asia 2018

Improving margins with new technologies, solutions and application methods 6-7 February 🚯 Singapore

SPECIALTY FERTILIZERS | NPK | MICRONUTRIENTS | BIOSTIMULANTS

The Summit will cover:

Market and Trade Dynamics Political and Regulatory Impact Advanced NPK Compounds Primary Nutrients Water Soluble Fertilizers Enhanced Efficiency Fertilizers (EEF) Ca/Mg/S and Micronutrients New Concept Fertilizers Biostimulants

integer

SELECTION OF KEY SPEAKERS Kewala N.Joshi, Senior General Manager, Commercial, IFFCO Grant Roberts, Chief Agronomist, Asia, Yara Markus Schmid, Head of Global Marketing Soil Manager, BASF Ross Gilmour, Senior Agronomist, Koch Industries

What past attendees say about Integer's Value Added Fertilizer Summits...

Stimulating. Excellent! Great K+S Asia Pacific participation! Very informative! International Finance Corporation (IFC) A well organized and informative summit. Great opportunity to meet

others in the industry. Great to learn of difficulties we all face in marketing these products.

> Excellent summit for new information and networking. Coromandel International Limited

> > Lunch sponsor

debottlenecking

NITROGEN+SYNGAS **NOVEMBER-DECEMBER 2017**

BCInsight

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577 Web: www.bcinsight.com www.bcinsightsearch.com

Early Bird Discount SAVE \$300

Book your discounted delegate ticket: www.integer-research.com/conferences/vafsa-2018 **Request more information:** conferences@integer-research.com | +44 20 7503 1265 *Early Bird Discount must end 17th November 2017. For group ticket discounts please contact us.

\$300

Discount!

CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant

Stanley Agriculture Group An excellent collection of talent, new product initiatives, networking with producers, clearing doubts.

very impressive.

A lot of new technology.

Exhibition sponsor

AGRIALGAE'

ENVIRONMENTAL COMPLIANCE, SAFETY, RELIABILITY

are the finest ingredients for durable industrial investments.

Eurotecnica's high-end technologies grant a perfect combination between sustainability and profitability, as companies the likes of QAFCO, ADNOC Takreer, Xinjiang Xinlianxin, MHTL Trinidad, Grupa Azoty can witness.

EUROMEL® Melamine Process, the leading technology for the production of crystal melamine from urea or ammonia, is the only melamine process featuring total zero pollution.

ET Black™ Carbon Process is the technology of reference for producing carbon black, a widely used chemical obtained by thermal decomposition of highly aromatic oils such as FCC decant oil, Ethylene Tars, Coal Tars.

ET Sun Energy^m **Process** is used to implement the thermal energy storage systems applied at CSP solar power plants for enhancing the electric power dispatchability.

Ask for more information. Visit us on www.eurotecnica.it

HIGH-END TECHNOLOGIES BY EUROTECNICA

17

18

19

20

21

22

23

24

25

26

27

28 29

30

Don't forget the next issue of Nitrogen+Syngas January/February 2018

■ CONTENTS

What's in issue 350

COVER FEATURE 1

Power to ammonia

COVER FEATURE 2

Prospects for Indian urea

COVER FEATURE 3

Fertilizers from gasification

COVER FEATURE 4

Nitrate plant debottlenecking

Southbank House, Black Prince Road London SE1 7SJ, England Tel: +44 (0)20 7793 2567 Fax: +44 (0)20 7793 2577

Web: www.bcinsight.com www.bcinsightsearch.com